Product Environmental Aspects **Declaration**

EP and IJ printer (PCR number: AD-04)



No. AD-12-195 Date of publication Jul./4/2012



http://www.brother.co.jp/

For inquiry:

Environmental Product Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2406 FAX: +81-52-824-5667


Black & White Laser Printer HL-6180DW Specifications:

- · Electrophotographic Printer (EP)
- Black & White
- Printing Speed: 40ppm Maximum Printing Size: A4
- Duplex Printing

The following data is calculated by assuming the product prints 960,000 sheets in 5-year usage period. < Main environmental impact in the product lifecycle >

- 23.900MJ
- Energy consumption Global warming impact (CO₂ equivalent)
 - 1,329.4kg 2.00kg
- Acidification impact (SO₂ equivalent)





- Electric power consumption in 5 years of "Use stage" is 591kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR:Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

[Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025 🗆 internal 🔳 external Third party verifier *: System auditor, Shozo Nakamuta

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

^{*} In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



| Document control no. | F-02As-02 |
|--------------------------|-------------------------|
| Product vendor | Brother Industries,LTD. |
| EcoLeaf registration no. | AD-12-195 |

| Unit Function DB version | v2.1 |
|------------------------------------|------|
| Characterization Factor DB version | v2.1 |

| PCR name | EP and IJ print | Product type | HL-6180DW | | | | |
|----------|-----------------|---------------------|-----------|--------------|-----|-------------------|------|
| PCR code | AD-04 | Product weight (kg) | 11.6 | Package (kg) | 2.2 | Weight total (kg) | 13.8 |

| Life Cycle Stage | | | | | Unit | Produ | ıction | Biotoli otton | | D' | T. () |
|----------------------|---|-----------------------|---------------------|---|------|--------------|----------|---------------|----------|----------|----------|
| In/Out | In/Out items | | | | | Raw material | Product | Distribution | Use | Disposal | Total |
| Energy Consumption | | | | | MJ | 1.46E+03 | 1.36E+02 | 3.92E+01 | 2.22E+04 | 1.30E+01 | 2.39E+04 |
| | | Lileig | | <u> </u> | Mcal | 3.50E+02 | 3.26E+01 | 9.35E+00 | 5.31E+03 | 3.10E+00 | 5.70E+03 |
| | | | es es | Coal | kg | 7.46E+00 | 8.81E-01 | 9.14E-05 | 1.08E+02 | 7.81E-02 | 1.16E+02 |
| | | | Energy resources | Crude oil (for fuel) | kg | 1.44E+01 | 1.14E+00 | 8.55E-01 | 1.98E+02 | 1.39E-01 | 2.14E+02 |
| | | | Sol | LNG | kg | 2.97E+00 | 4.60E-01 | 1.32E-02 | 4.30E+01 | 4.02E-02 | 4.65E+01 |
| | | | e e | Uranium content of an ore | kg | 2.90E-04 | 5.96E-05 | 6.20E-09 | 4.68E-03 | 5.28E-06 | 5.04E-03 |
| | | | | Crude oil (for material) | kg | 6.94E+00 | 3.53E-03 | 0 | 8.65E+01 | 0 | 9.35E+01 |
| | | | | Iron content of an ore | kg | 3.67E+00 | 0 | 0 | 4.11E+01 | 0 | 4.47E+01 |
| | | Exhaustible resources | | Cu content of an ore | kg | 1.99E-01 | 0 | 0 | 1.33E-01 | 0 | 3.32E-01 |
| | Se | ž | | Al content of an ore | kg | 1.20E-01 | 0 | 0 | 1.80E+00 | 0 | 1.92E+00 |
| | שַׁ בַּ | esc | SS | Ni content of an ore | kg | 1.10E-02 | 0 | 0 | 1.62E-01 | 0 | 1.73E-01 |
| | Impact by Resource Consumption | 0 | Mineral resources | Cr content of an ore | kg | 1.59E-02 | 0 | 0 | 2.33E-01 | 0 | 2.49E-01 |
| | A E | igi | ınc | Mn content of an ore | kg | 1.88E-02 | 0 | 0 | 2.42E-01 | 0 | 2.60E-01 |
| | by Isu | nst | esc | Pb content of an ore | kg | 9.32E-03 | 0 | 0 | 4.87E-03 | 0 | 1.42E-02 |
| | j g | hal | ౼ | Sn content of an ore | kg | - | ı | - | - | - | |
| | <u>ğ</u> 0 | Ж | era | Zn content of an ore | kg | 9.18E-02 | 0 | 0 | 4.80E-02 | 0 | 1.40E-01 |
| | 드 | | ĕ | Au content of an ore | kg | - | ı | - | - | - | |
| | | | _ | Ag content of an ore | kg | - | - | - | - | - | |
| | | | | Silica Sand | kg | 3.08E-01 | 0 | 0 | 6.95E-01 | 0 | 1.00E+00 |
| es | | | | Halite | kg | 1.81E+00 | 1.06E-04 | 0 | 7.19E+00 | 4.25E-03 | 9.01E+00 |
| . <u>s</u> | | | | Limestone | kg | 9.41E-01 | 6.89E-03 | 0 | 1.08E+01 | 1.08E-01 | 1.19E+01 |
| Inventory anaiyses | | | | Natural soda ash | kg | 2.60E-02 | 0 | 0 | 2.28E-02 | 0 | 4.88E-02 |
| a | | Renev | wable | Wood | kg | 3.83E+00 | 2.08E-01 | 0 | 1.59E+02 | 0 | 1.63E+02 |
| 6 | | resou | ırces | Water | kg | 7.31E+03 | 6.80E+02 | 6.92E-02 | 7.38E+04 | 6.60E+01 | 8.19E+04 |
| ţ | | | | CO2 | kg | 7.41E+01 | 7.51E+00 | 2.78E+00 | 1.21E+03 | 1.16E+01 | 1.31E+03 |
| ĭ ĕ | | | | SOx | kg | 4.66E-02 | 5.45E-03 | 1.60E-03 | 7.45E-01 | 6.09E-03 | 8.04E-01 |
| <u> =</u> | | | | NOx | kg | 9.67E-02 | 5.44E-03 | 1.17E-02 | 1.58E+00 | 1.30E-02 | 1.71E+00 |
| | | to | _ | N2O | kg | 6.92E-03 | 2.12E-04 | 4.89E-04 | 7.28E-02 | 1.73E-05 | 8.05E-02 |
| | e g | Atmosphere | | CH4 | kg | 7.74E-04 | 1.60E-04 | 1.66E-08 | 1.25E-02 | 1.41E-05 | 1.34E-02 |
| | arc | | | CO | kg | 9.16E-03 | 1.13E-03 | 2.73E-03 | 2.26E-01 | 2.39E-03 | 2.42E-01 |
| | Emission/Discharge e environment | | | NMVOC | kg | 1.51E-03 | 3.12E-04 | 3.24E-08 | 2.45E-02 | 2.77E-05 | 2.63E-02 |
| | Dis Tet | | | CxHy | kg | 3.26E-03 | 6.40E-05 | 3.73E-04 | 3.67E-02 | 4.57E-05 | 4.04E-02 |
| | y Emission/Disc the environment | | | Dust | kg | 1.02E-02 | 3.02E-04 | 1.15E-03 | 1.29E-01 | 7.42E-04 | 1.42E-01 |
| | ssic | | | BOD | kg | - | - | - | - | - | |
| | e iii | to | _ | COD | kg | - | - | - | - | - | |
| | | ں Water o | - | N total | kg | - | - | - | - | - | |
| | t by | water | Jonalii | P total | kg | - | - | - | - | - | |
| | act | | | SS | kg | - | - | - | - | - | |
| | Impact by to th | | | Unspecified Solid Waste | kg | 5.91E-01 | 2.58E-03 | 0 | 7.86E+01 | 5.32E+00 | 8.45E+01 |
| | = | | | Slag | kg | 1.28E+00 | 0 | 0 | 1.26E+01 | 0 | 1.38E+01 |
| | | to | 0 | Sludge | kg | 1.77E-01 | 0 | 0 | 3.79E+00 | 0 | 3.97E+00 |
| | | Soil sy | ystem | Low level | | | | | | | |
| | | | | radio-active waste | kg | 2.03E-04 | 4.17E-05 | 4.33E-09 | 3.27E-03 | 3.69E-06 | 3.52E-03 |
| | | | | | | | | | | | |
| | by Resource Consumption | | | Energy resources (crude oil equivalent) | kg | 2.52E+01 | 2.75E+00 | 8.71E-01 | 3.57E+02 | 2.80E-01 | 3.86E+02 |
| | dwn | Exhau | | (orado on equivalent) | | | | | | | |
| ŧ | y Re cons | resou | ırces | Mineral resources | kg | 6.09E+01 | 1.94E-03 | 0 | 2.53E+02 | 0 | 3.14E+02 |
| act | | | | (Iron ore equivalent) | i.g | 0.002.01 | 1.042 00 | ŭ | 2.002.02 | Ů | 0.142.02 |
| Impact assessment | Impact by Emission/Discharge to the environment | | | Global Warming | | 7.007.04 | | 0.045.00 | | | 1 005 00 |
| ass. | by sche | | | (CO2 equivalent) | kg | 7.60E+01 | 7.57E+00 | 2.91E+00 | 1.23E+03 | 1.16E+01 | 1.33E+03 |
| | pact on/Di envir | Atmos | | | | | | | | | |
| | In Inssic the | | | Acidification | kg | 1.14E-01 | 9.26E-03 | 9.76E-03 | 1.85E+00 | 1.52E-02 | 2.00E+00 |
| | En | | | (SO2 equivalent) | | | | | | | |

[Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage. C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel. C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.

 B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

 C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- 1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photoreceptor, as well as the impact of product assembly
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance The transportation distance in Japan uses 100 km as average distance
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 960,000 sheets, calculated by supposing a user use a machine for 5 years.
- It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure. The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

- The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance
- Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.
- 5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.
- This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines

Product data sheet

Input data and parameters for I CA

| | (input data and parameters for LCA) |
|--------------------------|-------------------------------------|
| Document control no. | F-03s-02 |
| Product vendor | Brother Industries,LTD. |
| EcoLEaf registration no. | AD-12-195 |



| PCR name | EP and IJ printer(PCR ID:AD-04) | Product type | | | HL-6180 | ow . | |
|-----------------------|---------------------------------|---------------------|------|--------------|---------|-------------------|------|
| LCA/LCIA in units of: | 1 | Product weight (kg) | 11.6 | Package (kg) | 2.2 | Weight total (kg) | 13.8 |

1. Product information (per unit): parts etc. by material and by process/assembly method

| | | Breakdown of p | rimary materials | | Math breakdown of parts, which | ch need to apply | Processing / Assembly Base Ur | nits (Parts B, C) |
|-------|---------------------|----------------|-------------------------|-------------|---|------------------|-------------------------------|-------------------|
| | Material name | Weight (kg) | Material name | Weight (kg) | Process name | Weight (kg) | Process name | Weight (kg) |
| | Steel | 3.07E+00 | Paper | 1.79E+00 | Press molding: Iron (kg) | 3.14E+00 | Parts assembly (kg) | 1.58E+00 |
| | Stainless steel | 6.89E-02 | Semiconductor substrate | 8.32E-01 | Press molding: Nonferrous metal (kg) | 7.79E-02 | | |
| ಕ | Aluminum | 7.79E-02 | Wood | 0 | Injection molding (kg) | 7.33E+00 | | |
| про | Other metal | 0 | Medium-sized motor | 4.26E-01 | Glass molding (kg) | 6.34E-02 | | |
| 풉 | Thermoplastic resin | 7.18E+00 | Lubricants | 5.43E-03 | | | | |
| | Thermosetting resin | 4.50E-03 | | | | | | |
| | Rubber | 2.35E-01 | | | | | | |
| | Glass | 6.34E-02 | | | | | | |
| | Subtotal | 1.07E+01 | Subtotal | 3.05E+00 | | | | |
| | | Total | | 1.38E+01 | Subtotal | 1.06E+01 | Subtotal | 1.58E+00 |
| MI-A- | | | | | | | | |

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

| | Classification | Material | Energy | Energy | Energy | Energy | Energy | Energy | Energy |
|---------|----------------|-----------------------------|-------------------------------|---------------------------------|---------------------------------|---------------------|--|------------------------|----------------------------|
| _ | Distribution | Corrugated cardboard (kg) | Electricity (kwh) | Diesel truck: 10 ton (kg.km) | Diesel truck: 2 ton (kg.km) | LNG as fuel (kg) | Diesel oil as fuel (kg) | Heavy oil fuel (kg) | Freight by ship (kg.km) |
| Ë | Quantity | 9.28E-02 | 4.05E+00 | 1.13E+01 | 4.00E+01 | 1.60E-02 | 1.40E-02 | 6.27E-02 | 4.75E+02 |
| umption | Note | | | | | | | | |
| | Classification | Material | Material | Energy | Energy | Material | Energy | | |
| Cons | Distribution | Raw wood (Imported) (kg) | Low density polyethylene (kg) | LPG(NPG) as fuel (kg) | Diesel truck: 20 ton (kg.km) | PP (kg) | Incineration: Industrial waste (kg) | | |
| | Quantity | 1.00E-02 | 1.17E-03 | 1.32E-02 | 1.80E+01 | 2.38E-03 | 1.06E-01 | | |
| | Note | | | | | | | | |
| arge | Classification | | | | | | | | |
| Disch | Distribution | | | | | | | | |
| /wols | Quantity | | | | | | | | |
| SII. | Note | | | | | | | | |

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

| | Means of transportation | Diesel truck: | Diesel truck: | Diesel truck: | Diesel truck: | Freight by | Freight by | Freight by | Freight by |
|------------|-------------------------|----------------|----------------|--------------------|----------------|--------------|---------------|--------------------|--------------|
| | | 20 ton (kg.km) | 20 ton (kg.km) | 20 ton (kg.km) | 20 ton (kg.km) | ship (kg.km) | ship (kg.km) | ship (kg.km) | ship (kg.km) |
| | Conditions | Mass (kg) | Distance (km) | Loading Ratio (%w) | Load (kg·km) | Mass (kg) | Distance (km) | Loading Ratio (%w) | Load (kg·km) |
| . <u>e</u> | Quantity | 1.38E+01 | 5.00E+01 | 3.58E+01 | 1.92E+03 | 1.38E+01 | 3.30E+03 | 1.00E+02 | 4.54E+04 |
| 풀 | Note | | | | | | | | |
| i i | Means of transportation | Diesel truck: | Diesel truck: | Diesel truck: | Diesel truck: | | | | |
| E | means of transportation | 10 ton (kg.km) | 10 ton (kg.km) | 10 ton (kg.km) | 10 ton (kg.km) | | | | |
| | Conditions | Mass (kg) | Distance (km) | Loading Ratio (%w) | Load (kg·km) | | | | |
| | Quantity | 1.38E+01 | 1.00E+02 | 3.58E+01 | 3.85E+03 | | | | |
| | Note | _ | | | | | | | |

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

| | Classification | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption |
|---------|----------------|---|---|---|---|---|--|--|---------------------------|
| | Distribution | Diesel truck: | Freight by | Diesel truck: | Diesel truck: | Cold-Rolled | Electroplated | Stainless | Aluminum |
| | Distribution | 20 ton (kg.km) | ship (kg.km) | 2 ton (kg.km) | 10 ton (kg.km) | steel plate (kg) | steel Plate (kg) | steel plate (kg) | plate (kg) |
| | Quantity | 4.34E+04 | 7.58E+05 | 1.96E+03 | 9.40E+04 | 3.76E+00 | 3.51E+01 | 1.02E+00 | 1.67E+00 |
| | Note | Distribution of consumables used in 5 years | | | | |
| | Classification | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption |
| | Distribution | Glass (kg) | Low density polyethylene (kg) | High density polyethylene (kg) | PP (kg) | PS (kg) | PBT (kg) | Polycarbonate (kg) | MMA resin (kg) |
| | Quantity | 1.44E-01 | 4.16E+00 | 3.46E-02 | 4.45E+00 | 3.62E+01 | 4.33E-02 | 3.29E+00 | 1.39E-02 |
| | Note | | | | | | | | |
| | Classification | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption |
| Product | Distribution | PC-ABS (70/30) (kg) | ABS (kg) | AS resin (kg) | POM (polyacetal) (kg) | PET (kg) | Expandable soft polyurethane (for automobile) (kg) | Nitrile-butadiene rubber(NBR) (kg) | Corrugated cardboard (kg) |
| ᄺ | Quantity | 5.06E-01 | 2.87E+00 | 2.24E+01 | 3.70E+00 | 3.44E+00 | 8.14E-01 | 1.03E+01 | 7.39E+01 |
| | Note | | | | | | | | |
| | Classification | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption |
| | Distribution | Paper (Western style) (kg) | Assembled circuit board (kg) | Medium-sized motor (kg) | Injection molding (kg) | Press molding: Iron (kg) | Press molding: Nonferrous metal (kg) | Glass molding (kg) | Parts assembly (kg) |
| | Quantity | 9.60E-01 | 4.35E-01 | 3.69E-01 | 6.90E+01 | 3.64E+01 | 1.67E+00 | 1.44E-01 | 3.07E+01 |
| | Note | | | | | | | | |
| | Classification | Consumption | Consumption | Consumption | Consumption | Consumption | Consumption | Process | |
| | Distribution | Electricity (kWh) | Diesel oil as fuel (kg) | Heavy oil as fuel (kg) | LNG as fuel(kg) | LPG(NPG) as fuel (kg) | Electricity (kWh) | Incineration: Industrial waste (kg) | |
| | Quantity | 5.91E+02 | 1.87E-01 | 1.57E+01 | 4.96E-01 | 1.78E-01 | 2.90E+02 | 5.17E+00 | |
| | Note | Electricity consumption for 5 years | Production of consumables used in 5 years | Production of consumables used in 5 years | Production of consumables used in 5 years | Production of consumables used in 5 years | Production of consumables used in 5 years | Packaging materials for distribution of ingredient | |

Note: At "Use Stage", the product electricity consumption in 5 years usage period is 591 kWh .

1.2 Disposition/Recycle information on consumables and replacement parts

| 4.2 | DIS | Josition/Recy | cie illiorillation on | consumables and i | epiacement parts | | | |
|--------|------|----------------|-----------------------|-------------------|------------------------|--------------------|--|---|
| mables | S | Classification | Consumption | Process | Process | Process | | |
| | ple | Distribution | Diesel truck: | Shredding (kg) | Incineration to | Landfill: | | |
| | na | | 4 ton (kg·km) | Officuality (kg) | landfill (as ash) (kg) | General waste (kg) | | |
| | sul | Quantity | 1.04E+04 | 1.07E+02 | 1.37E+02 | 4.95E+01 | | |
| | Cons | Note | Consumables not | Consumables not | Consumables not | Consumables not | | |
| | | | collected | collected | collected | collected | | 1 |

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

| J. Diap | osition/recyc | ie stage information | (per product), pro | cess method and s | cenanos | | |
|---------|----------------|---------------------------|------------------------|------------------------|------------------------|--|--|
| | Classification | Consumption | Process | Process | Process | | |
| .0 | Distribution | Diesel truck: | Shredding (kg) | Incineration to | Landfill: | | |
| ari | Distribution | 4 ton (kg.km) | Officading (kg) | landfill (as ash) (kg) | General waste (kg) | | |
| ie i | Quantity | 1.21E+03 | 1.03E+01 | 8.47E+00 | 4.01E+00 | | |
| Š | Note | Machines not collected | Machines not collected | Machines not collected | Machines not collected | | |

Note