

# Product Environmental Aspects Declaration



EP and IJ printer ( PCR number: AD-04 )

No. AD-18-E1080  
Date of publication  
Sep./14/2018

**brother**  
at your side

<http://www.brother-usa.com/>

For inquiry:  
Environmental Product Group  
Production Innovation Dept.  
Quality, Production & Engineering Center  
Brother Industries, Ltd.  
Tel: +81-52-824-2511 (Representative)  
Fax: +81-52-824-5166

## Color Printer HL-L3210CW


### Specifications:

- Electrophotographic Printer (EP)
- Color
- Printing Speed: 18 ppm in both color and black ( A4 )
- Maximum Printing Size: Legal
- Flexible Wireless Interface

The following data is calculated by assuming the product prints 194,400 sheets in 5-year usage period.

### < Main environmental impact in the product lifecycle >

- Energy consumption **20,200MJ**
- Global warming impact (CO<sub>2</sub> equivalent) **1,268.6kg**
- Acidification impact (SO<sub>2</sub> equivalent) **1.98kg**



- Electric power consumption in 5 years of “Use stage” is 216kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

### Notes:

1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR:Product Category Rule. Visit EcoLeaf website under JEMAI homepage at <http://www.ecoleaf-jemai.jp/eng/> for details.
3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

### [Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001.  
The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025  internal  external Third party verifier \*: System auditor, Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: [ecoleaf@jemai.or.jp](mailto:ecoleaf@jemai.or.jp)

\* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.  
The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AD-18-E1080

Unit Function DB version	v2.1
Characterization Factor DB version	v2.1

PCR name	EP and IJ printer		Product type	HL-L3210CW			
PCR code	AD-04	Product weight (kg)	17.37	Package (kg)	3.77	Weight total (kg)	21.14

Life Cycle Stage	Unit	Production		Distribution	Use	Disposal	Total			
		Raw material	Product							
<b>Energy Consumption</b>										
	MJ	2.20E+03	2.80E+02	8.96E+01	1.76E+04	1.80E+01	2.02E+04			
	Mcal	5.25E+02	6.70E+01	2.14E+01	4.20E+03	4.29E+00	4.82E+03			
Inventory analyses	by Resource Consumption	Energy resources	Coal	kg	1.28E+01	1.74E+00	2.09E-04	8.99E+01	1.07E-01	1.05E+02
			Crude oil (for fuel)	kg	2.11E+01	2.17E+00	1.96E+00	1.68E+02	1.94E-01	1.94E+02
			LNG	kg	4.97E+00	9.66E-01	3.02E-02	3.19E+01	5.51E-02	3.79E+01
			Uranium content of an ore	kg	4.32E-04	1.18E-04	1.42E-08	3.08E-03	7.23E-06	3.64E-03
			Crude oil (for material)	kg	9.20E+00	6.17E-06	0	7.37E+01	0	8.29E+01
		Iron content of an ore	kg	6.24E+00	0	0	4.70E+01	0	5.32E+01	
		Cu content of an ore	kg	2.89E-01	0	0	2.10E-02	0	3.10E-01	
		Al content of an ore	kg	5.42E-01	0	0	2.26E+00	0	2.80E+00	
		Ni content of an ore	kg	5.31E-02	0	0	1.36E-01	0	1.90E-01	
		Cr content of an ore	kg	7.39E-02	0	0	2.01E-01	0	2.75E-01	
	Mn content of an ore	kg	3.81E-02	0	0	2.71E-01	0	3.09E-01		
	Pb content of an ore	kg	1.36E-02	0	0	1.70E-03	0	1.53E-02		
	Sn content of an ore	kg	-	-	-	-	-	-		
	Zn content of an ore	kg	1.34E-01	0	0	1.68E-02	0	1.50E-01		
	Au content of an ore	kg	-	-	-	-	-	-		
	Ag content of an ore	kg	-	-	-	-	-	-		
	Silica Sand	kg	4.71E-01	0	0	6.12E-01	0	1.08E+00		
	Halite	kg	2.49E+00	1.02E-04	0	8.44E+00	6.84E-03	1.09E+01		
	Limestone	kg	1.60E+00	6.63E-03	0	1.24E+01	1.45E-01	1.42E+01		
	Natural soda ash	kg	3.97E-02	0	0	6.17E-03	0	4.58E-02		
Wood	kg	6.70E+00	1.85E-01	0	1.91E+02	0	1.98E+02			
Water	kg	1.14E+04	1.33E+03	1.59E-01	5.53E+04	9.03E+01	6.81E+04			
Impact by Emission/Discharge to the environment	to Atmosphere	CO2	kg	1.14E+02	1.46E+01	6.37E+00	1.10E+03	1.57E+01	1.25E+03	
		SOx	kg	8.43E-02	1.06E-02	3.34E-03	6.44E-01	8.25E-03	7.51E-01	
		NOx	kg	1.51E-01	1.02E-02	2.11E-02	1.56E+00	1.78E-02	1.76E+00	
		N2O	kg	1.04E-02	5.90E-04	1.20E-03	6.75E-02	2.42E-05	7.97E-02	
		CH4	kg	1.15E-03	3.15E-04	3.79E-08	8.19E-03	1.93E-05	9.67E-03	
		CO	kg	1.67E-02	2.25E-03	3.71E-03	2.23E-01	3.32E-03	2.49E-01	
		NMVOc	kg	2.24E-03	6.17E-04	7.43E-08	1.60E-02	3.79E-05	1.89E-02	
		CxHy	kg	4.82E-03	1.40E-04	7.66E-04	3.51E-02	6.63E-05	4.09E-02	
		Dust	kg	1.59E-02	5.58E-04	2.23E-03	1.25E-01	1.02E-03	1.45E-01	
		BOD	kg	-	-	-	-	-	-	
to Water domain	COD	kg	-	-	-	-	-			
	N total	kg	-	-	-	-	-			
	P total	kg	-	-	-	-	-			
to Soil system	SS	kg	-	-	-	-	-			
	Unspecified Solid Waste	kg	1.19E+00	1.95E-03	0	8.64E+01	8.56E+00	9.61E+01		
	Slag	kg	2.16E+00	0	0	1.43E+01	0	1.65E+01		
	Sludge	kg	1.05E+00	0	0	4.84E+00	0	5.89E+00		
Low level radio-active waste	kg	3.02E-04	8.23E-05	9.91E-09	2.15E-03	5.05E-06	2.54E-03			
Impact assessment	Exhaustible resources	Energy resources (crude oil equivalent)	kg	3.88E+01	5.41E+00	1.99E+00	2.89E+02	3.88E-01	3.36E+02	
		Mineral resources (iron ore equivalent)	kg	1.19E+02	3.39E-06	0	2.13E+02	0	3.32E+02	
	to Atmosphere	Global Warming (CO2 equivalent)	kg	1.17E+02	1.47E+01	6.69E+00	1.11E+03	1.57E+01	1.27E+03	
		Acidification (SO2 equivalent)	kg	1.90E-01	1.77E-02	1.81E-02	1.74E+00	2.07E-02	1.98E+00	

[Notes for readers: EcoLeaf common rules]

I. Stage related

A. "Production" stage is intended for two sub-stages listed below.

- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.

B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.

C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).

D. "Disposition" stage is intended for environmental impacts by product disposition.

II. Inventory analyses

A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.

B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.

C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/dischage to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV. Data entry format

A. Exponential notation, after the decimal point to two, should be used.

B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data).

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethy

2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.

3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.

The transportation distance in Japan uses 100 kmas average distance

4. Use stage's impact is calculated according to the PCR. It includes the impact of printing 194,400 sheets, calculated by supposing a user use a machine for 5 years.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a month consists of 4 weeks, with weekly electricity consumption calculated by the TEC test procedure.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.

Since we have not collected consumables as a producer, which are newly introduced, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AD-18-E1080

PSC name	EP and IJ printer(PCR ID:AD-04)	Product type	HL-L3210CW				
LCA/LCIA in units of:	1	Product weight (kg)	17.37	Package (kg)	3.77	weight total (kg)	21.14

1. Product information (per unit): parts etc. by material and by process/assembly method

Product	Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly base Units (Parts B.C)			
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	5.27E+00	Paper	3.14E+00	Press molding: Iron (kg)	5.61E+00	Parts assembly (kg)	3.87E+00
Stainless steel	3.35E-01	Semiconductor substrate	1.21E+00	Press molding: Nonferrous metal (kg)	2.08E-01			
Aluminum	4.61E-01	Medium-sized motor	6.16E-01	Injection molding (kg)	9.82E+00			
Other metal	3.01E-03	Lubricants	1.07E-02	Glass molding (kg)	1.17E-01			
Thermoplastic resin	9.61E+00							
Thermosetting resin	7.88E-02							
Rubber	2.99E-01							
Glass	1.17E-01							
Subtotal	1.62E+01	Subtotal	4.97E+00					
Total		Subtotal	2.11E+01	Subtotal	1.57E+01	Subtotal	3.87E+00	

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO2, NO2 equivalent.

Consumption	Classifier	Material	Energy	Energy	Energy	Energy	Energy	Energy	
	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 10 ton (kg/km)	Diesel truck: 4 ton (kg/km)	Incineration: Industrial waste (kg)	LNG as fuel (kg)	Diesel oil as fuel (kg)	Heavy oil fuel (kg)
	Quantity	7.28E-02	1.37E+01	1.97E+01	1.65E+02	1.02E-01	8.96E-02	2.15E-02	7.70E-02
Note									
Emission /discharge	Classifier	Energy	Material	Material	Energy	Material	Energy		
	Distribution	Freight by ship (kg,km)	Raw wood (foreign) (kg)	Low density polyethylene (kg)	LPG(NPG) as fuel (kg)	Diesel truck: 20 ton (kg,km)	PP (kg)	Injection molding (kg)	
	Quantity	1.02E+03	2.96E-02	2.05E-06	4.14E-02	6.77E+01	4.16E-06	6.20E-06	
Note									

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Classifier	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
	Quantity	2.11E+01	7.00E+01	4.81E+01	3.08E+03	2.11E+01	5.30E+03	1.00E+02	1.12E+05
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg,km)	Freight by ship (kg,km)	Diesel truck: 10 ton (kg,km)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)	Copper plate (kg)
	Quantity	2.16E+02	5.78E+04	1.15E+06	8.26E+04	4.51E+01	8.57E-01	2.13E+00	1.88E-02
Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years					
Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	Glass (kg)	High density polyethylene (kg)	Low density polyethylene (kg)	PP (kg)	PS (kg)	PBT(Poly Butylene Terephthalate) (kg)	Polycarbonate (kg)	PC-ABS(70/30)(kg)
	Quantity	4.08E-02	2.65E-02	4.70E+00	7.69E+00	3.19E+01	3.07E-02	3.58E+00	9.33E-01
Note									
Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	POM(polyacetal) (kg)	ABS (kg)	AS resin (kg)	PA66 (Polyamide 66) (kg)	PET (kg)	Acrylonitrile-butadiene copolymer (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)
	Quantity	4.41E+00	2.63E+00	1.39E+01	7.08E-02	2.17E+00	1.07E+00	5.85E+00	8.55E+01
Note									
Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	Paper (Western style)	Assembled circuit board(kg)	Press molding: Iron (kg)	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Glass molding (kg)	Parts assembly (kg)	Electricity (kwh)
	Quantity	3.27E+00	1.11E-01	4.63E+01	6.64E-01	6.76E+01	4.08E-02	3.87E+01	2.22E+02
Note								Production of consumables used in 5 years	
Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	
	Distribution	Diesel truck: 20 ton (kg,km)	Freight by ship (kg,km)	Diesel truck: 10 ton (kg,km)	Heavy oil fuel (kg)	Diesel oil as fuel (kg)	LPG(NPG) as fuel (kg)	LNG as fuel (kg)	Low density polyethylene (kg)
	Quantity	4.23E+02	5.14E+04	1.74E+03	7.90E+00	2.81E-01	5.38E-01	5.63E-01	1.81E-04
Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	
Product	Classifier	Consumption	Consumption	Consumption	Consumption	Consumption	Process		
	Distribution	PP (kg)	Raw wood (foreign) (kg)	Corrugated cardboard (kg)	Injection molding (kg)	Diesel truck: 4 ton (kg,km)	Incineration: Industrial waste (kg)		
	Quantity	3.68E-04	1.85E-01	4.56E-01	5.49E-04	1.03E+03	6.41E-01		
Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Incineration to landfill (see ash) (kg)	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years			

Note Electric power consumption in 5 years of "Use stage" is 216kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classifier	Consumption	Process	Process	Process
	Distribution	Diesel truck: 4 ton (kg,km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)
	Quantity	3.08E+04	1.19E+02	1.85E+02	4.99E+01
Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected	

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

Scenario	Classifier	Consumption	Process	Process	Process
	Distribution	Diesel truck: 4 ton (kg,km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)
	Quantity	1.76E+03	1.45E+01	1.14E+01	6.79E+00
Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected	

Note

6. Others