

Product Environmental Aspects Declaration



EP and IJ printer (PCR-ID:AD-04)

No. AD-12-188
Date of publication
Oct./15/2012



KONICA MINOLTA

<http://konicaminolta.jp>

Please direct any inquiries or comments to e-mail:
bt-environ@pub.konicaminolta.jp



Total of 1,815,000 sheets on the assumption of five years usage.
Environmental impact by copypaper is not included

bizhub C554


Marking technologies Electrophotographic Printer (EP)
Printing speed 55 prints-per-minute(B/W), 55 prints-per-minute(color)
Maximum copy paper A3
Duplex copying Non-stack ADU equipped
Document feeding ADF with Auto-document reversing function equipped

Life Cycle Impact

Consumption and discharge in a life cycle	All the stage sum totals
Global warming(CO ₂ equivalent):kg	2,283 (1,930)
Acidification(SO ₂ equivalent):kg	3.6 (3.0)
Energy resources(crude oil equivalent):MJ	44,352 (36,482)

※Figures in () indicated environmental impact including recycle effect *note3

Warming load CO₂ equivalent of each stage (kg)



Notes:

- Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at <http://www.ecoleaf-jemai.jp/eng/> for details.
- Recycle Effect illustrates an indirect influence to other products/services.
- Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.

【Supplemental environmental information】



- Certified Environmental Standards
 - Japan Eco Mark
 - International Energy Star Program
- Conforming to Japanese Law on Promoting Green Purchasing

PCR review was conducted by : PCR Deliberation Committee, January 01, 2008, Name of representative : Youji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the declaration and data, according to ISO14025 internal external

Third party verifier: The third party verifier * : Shozo Nakamuta

Programme operator: Japan Environmental Management Association for Industry, ecoleaf@jemai.or.jp

* In the case of an business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)

Document control no.	F-02B-03
Product vendor	KONICA MINOLTA, INC.
EcoLeaf registration no.	AD-12-188

Unit Function DB version	2.1
Characterization Factor DB version	2.1



PCR name	EP and IJ printer	Product type	bizhub C554				
PCR-ID	AD-04	Product weight[kg]	101.0	Package[kg]	24.0	Weight total[kg]	125.0

In/Out items	Life Cycle Stage	Unit	Production		Distribution	Use	Disposal	Recycle		
			Raw material	Product						
Energy Consumption										
Inventory analyses	Resource Consumption from the environment	Energy	MJ	9.53E+03	1.53E+03	2.03E+02	3.30E+04	9.88E+01	-7.87E+03	
			Mcal	2.28E+03	3.67E+02	4.85E+01	7.88E+03	2.36E+01	-1.88E+03	
			kg	7.39E+01	9.99E+00	4.74E-04	1.56E+02	5.13E-01	-4.86E+01	
			kg	8.97E+01	1.13E+01	4.43E+00	2.46E+02	1.05E+00	-5.94E+01	
			kg	1.76E+01	5.10E+00	6.84E-02	5.81E+01	2.65E-01	-6.87E+00	
		mg	1.77E-03	6.76E-04	3.21E-08	6.41E-03	3.47E-05	-3.95E-04		
		Exhaustible resources	Material	kg	3.57E+01	0	0	1.89E+02	0	-7.08E+01
				kg	5.53E+01	0	0	5.66E+01	0	-4.47E+01
				kg	2.26E+00	0	0	2.11E-04	0	-7.34E-01
				kg	1.60E+00	0	0	3.65E+00	0	-2.10E+00
				kg	1.85E-01	0	0	1.45E+00	0	-6.54E-01
				kg	2.68E-01	0	0	1.98E+00	0	-9.00E-01
				kg	2.93E-01	0	0	5.34E-01	0	-1.20E-01
				kg	9.88E-02	0	0	0	0	-2.69E-02
				kg	0	0	0	0	0	0
	kg			9.72E-01	0	0	0	0	-2.64E-01	
	Renewable resources		kg	0	0	0	0	0	0	
			kg	0	0	0	0	0	0	
			kg	0	0	0	0	0	0	
			kg	3.67E+00	0	0	6.80E-01	0	-1.20E+00	
kg			2.65E+01	1.78E-03	0	6.81E+00	3.59E-02	-1.27E+01		
Emission/Discharge to the environment	to Atmosphere	kg	1.18E+01	0	0	1.27E+01	5.53E-01	-7.46E+00		
		kg	3.13E-01	0	0	3.36E-03	0	-9.85E-02		
		kg	3.53E+01	0	0	7.66E+01	0	-4.48E+01		
		kg	4.19E+04	8.13E+03	3.58E-01	8.54E+04	4.20E+02	-1.28E+04		
		kg	5.26E+02	7.79E+01	1.44E+01	1.57E+03	5.44E+01	-3.42E+02		
		kg	3.42E-01	5.92E-02	9.19E-03	1.09E+00	2.93E-02	-2.34E-01		
		kg	6.26E-01	4.74E-02	7.55E-02	2.20E+00	7.06E-02	-5.31E-01		
		kg	4.30E-02	1.19E-03	2.31E-03	1.18E-01	9.72E-05	-4.07E-02		
		kg	4.72E-03	1.81E-03	8.59E-08	1.70E-02	9.29E-05	-1.01E-03		
		kg	7.23E-02	1.15E-02	2.12E-02	3.66E-01	1.49E-02	-5.26E-02		
	kg	9.24E-03	3.54E-03	1.68E-07	3.34E-02	1.82E-04	-1.98E-03			
	kg	2.10E-02	2.40E-04	2.17E-03	5.77E-02	4.06E-04	-1.98E-02			
	kg	6.98E-02	2.54E-03	7.08E-03	2.09E-01	4.10E-03	-6.61E-02			
	to Water system	kg	-	-	-	-	-	-		
		kg	-	-	-	-	-	-		
kg		-	-	-	-	-	-			
kg		-	-	-	-	-	-			
kg		-	-	-	-	-	-			
to Soil system	kg	3.62E+00	1.20E-02	0	6.24E+01	4.36E+01	-3.05E+00			
	kg	1.83E+01	0	0	1.81E+01	0	-1.34E+01			
	kg	2.44E+00	0	0	7.84E+00	0	-4.11E+00			
	kg	1.24E-03	4.72E-04	2.24E-08	4.47E-03	2.42E-05	-2.76E-04			
Impact assessment by Resource Consumption	Exhaustible resources	kg	1.73E+02	2.94E+01	4.51E+00	4.68E+02	1.98E+00	-1.02E+02		
		kg	7.15E+02	0	0	1.32E+03	0	-7.53E+02		
	to Atmosphere	kg	5.38E+02	7.83E+01	1.50E+01	1.60E+03	5.45E+01	-3.53E+02		
		kg	7.81E-01	9.24E-02	6.20E-02	2.63E+00	7.87E-02	-6.06E-01		
	to Water system									
	to Soil system									

[Notes for readers: EcoLeaf common rules]

I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
 - (1) "Raw material" production: consists of mining, transportation and raw material production.
 - (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts)
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal/recycle of consumables
- D. "Disposition/Recycle" stage is intended for environmental impacts by product disposition/recycle, and deduction by recycling
- E. "Recycle Effect" illustrates an indirect environmental influences to other products/services by use of reclaimed materials/parts, and/or by supply of
 - Case 1: Use of reclaimed materials/parts: Sum of increase of environmental impact by collection activities of used materials/parts, and decrease
 - Case 2: Supply of used products to other businesses for material reclaim/parts reuse: Sum of increase of environmental impact by materials/parts

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate,
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming")

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- A. "Raw material" in "Production" includes environmental impacts generated during mining - transportation - material production phases of the main body
- B. "Product" in "production" includes environmental impacts of processing of the parts (injection, blow-, press- and glass-molding).
- C. Regarding the basis and the basic units for calculations during distribution stages
- D. Regarding the basis and the basic units for calculations during use and consumption stage
- E. The recycling impacts are calculated assuming that 40% of the end-of-life printers are recovered from users according to PCR (AD-04).
- F. The impacts of material production of recycled materials are included in the values with minus as a recycling effect.

Product data sheet

(Input data and parameters for LCA)



Document control no.	F-03-03
Product vendor	KONICA MINOLTA, INC.
EcoLeaf registration no.	AD-12-188

PCR name	EP and IJ printer(PCR-ID:AD-04)	Product type	bizhub C554				
LCA/LCIA in units of:	1	Product weight[kg]	101.0	Package[kg]	24.0	Weight total[kg]	125.0

1. Product information (per unit): parts etc. by material and by process/assembly method

Breakdown of primary materials				Math breakdown of parts, which need to apply Processing / Assembly Base Units (Parts B, C)			
Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
Ordinary steel	5.27E+01	Rubber	7.20E-01	Press molding:Iron	4.84E+01	Parts assembly	1.19E+00
Stainless steel	1.17E+00	Semiconductor circuit board	4.28E+00	Press molding:Nonferrous metal	3.15E+00		
Aluminium	1.08E+00			Injection molding	3.70E+01		
Other metals	2.08E+00			Blow molding	6.80E-01		
Glass	2.47E+00			Glass molding	2.47E+00		
Thermoplastic resin	3.95E+01						
Wood	8.43E+00						
Paper	1.26E+01						
Subtotal	1.20E+02	Subtotal	5.00E+00				
Total		Total	1.25E+02	Subtotal	9.16E+01	Subtotal	1.19E+00

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

Consumption	Classification	Energy	Energy	Material	Material				
	Distribution	Electricity (kWh)	Furnace urban gas (m ³)	Industrial water(kg)	Groundwater (kg)				
	Quantity	7.90E+01	1.27E-01	3.17E+02	2.36E+02				
	Note								
Emission/Discharge	Classification	To Water system							
	Distribution	Sewage(kg)							
	Quantity	3.08E+02							
	Note								

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Distribution	Means of transportation	Freight by ship	Diesel truck :20ton	Diesel truck :2ton						
	Conditions	Load(kg·km)	Load(kg·km)	Load(kg·km)						
	Quantity	2.13E+05	4.98E+04	1.50E+03						
	Note									

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kWh)	Gasoline as fuel(kg)	Furnace urban gas (m ³)	Industrial water(kg)	Groundwater (kg)	Ordinary steel (kg)	Stainless steel (kg)	Aluminium (kg)
	Quantity	1.33E+03	4.68E+00	3.83E+00	3.51E+02	6.65E+03	5.17E+01	9.17E+00	3.46E+00
Product	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Processing	Processing
	Distribution	Copper(kg)	Glass (kg)	Thermoplastic resin(kg)	Wood(kg)	Paper(kg)	Rubber (kg)	Press:Iron (kg)	Press: Nonferrous(kg)
	Quantity	7.00E-04	4.00E-02	1.88E+02	5.41E+00	3.35E+01	4.72E+00	9.24E+01	3.43E+00
Product	Classification	Processing	Processing	Assembly	To Water system				
	Distribution	Injection molding(kg)	Blow molding (kg)	Parts assembly (kg)	Sewage (kg)				
	Quantity	1.94E+01	5.08E+01	5.08E+01	2.18E+03				
Product	Classification	Distribution	Distribution	Distribution					
	Distribution	Freight by ship (kg·km)	Diesel truck: 20ton (kg·km)	Diesel truck: 10ton (kg·km)					
	Quantity	5.19E+05	3.04E+05	3.48E+04					

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
	Quantity	6.98E+00	9.10E-02	2.44E+01	1.38E+00	2.80E-04	1.60E-02	5.84E+01	1.55E+01
Consumables	Classification	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction	Deduction
	Distribution	Industrial waste destruction by fire(kg)	Industrial waste innig(kg)	Waste destruction by fire(kg)	Waste innig(kg)	Iron(kg)	Aluminum(kg)	Copper(kg)	Glass(kg)
	Quantity	1.89E+00	5.90E-01	1.15E+02	3.86E+01	-2.44E+01	-1.38E+00	-2.80E-04	-1.60E-02
Consumables	Classification	Deduction	Deduction	Distribution	Distribution				
	Distribution	Plastics(kg)	Paper(kg)	Diesel truck: 10ton (kg·km)	Diesel truck: 4ton (kg·km)				
	Quantity	-5.84E+01	-1.55E+01	1.23E+04	1.48E+04				

5. Disposition/Recycle stage information (per product): process method and scenarios

Consumables	Classification	Consumption	Consumption	Treatment	Treatment	Treatment	Treatment	Treatment	Treatment
	Distribution	Electricity (kWh)	Kerosene(kg)	Recycle: to iron(kg)	Recycle: to Aluminum(kg)	Recycle: to copper(kg)	Recycle: to Glass(kg)	Recycle: to plastics(kg)	Recycle: to Paper(kg)
	Quantity	3.42E+00	4.45E-02	2.15E+01	4.30E-01	1.41E+00	9.87E-01	1.56E+01	9.01E+00
Consumables	Classification	Treatment	Treatment	Treatment	Treatment	Treatment	Deduction	Deduction	Deduction
	Distribution	Recycle: to Assembled circuit board(kg)	Incineration: Industrial waste(kg)	Landfill: Industrial waste(kg)	Incineration to landfill (as ash)(kg)	Landfill: General waste(kg)	Iron(kg)	Aluminium (kg)	copper(kg)
	Quantity	5.81E-01	1.33E+00	3.06E-01	3.68E+01	3.76E+01	-2.15E+01	-4.30E-01	-1.41E+00
Consumables	Classification	Deduction	Deduction	Deduction	Deduction	Distribution	Distribution		
	Distribution	Glass(kg)	Plastics(kg)	Paper(kg)	Recycle: to Assembled circuit board(kg)	Diesel truck: 10ton (kg·km)	Diesel truck: 4ton (kg·km)		
	Quantity	-9.87E-01	-1.56E+01	-9.01E+00	-5.81E-01	6.00E+03	7.26E+03		

6. Others

A.Product information:

All the parts mass per unit sorted by materials and by processes/assembly are included. The motor mass is included in ordinary steel.

B.Production site information:

The energy consumption & material use during the main body assembly and cartridge & toner shipment are included.
The environmental impacts that are exhausted from the production site in the atmosphere and the water system are included.

C.Distribution stage information:

The total distance of the transportation in Japan of 100km is used according to PCR (AD-04) and the transportation overseas includes the transportation by track in China and by ship between China and Japan.

D. Product and accessories subject to this analysis:

The power consumption is calculated assuming the use period of five years and 1,815,000 sheets printed during the use period according to the PCR (AD-04).
The toner consumption is summed up over the five years from the toner consumption data per sheet using our print pattern with 5% coverage.
The production impacts of the cartridges and toner used during the use period of five years are included.
The impacts of the maintenance parts used and the transportation impacts of the maintenance during the use period of five years are included in this stage.

E. Disposal/Recycle information on the consumables and the maintenance parts during use stage:

The recycling information of the toner, the developer, the drums and the maintenance parts used during the use period of five years are included .
The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.

F.Disposal/Recycle stage information:

The information on the products recovered from users is included.
The recycling processing impacts are included as plus and the production impacts of the recycled materials are included as minus.