Product Environmental Aspects Declaration

Facsimile (PCR number: AH-03)



No. AH-18-E220 Date of publication Jun./05/2018



http://www.brother-usa.com/

For inquiry:

Environmental Product Group Production Innovation Dept. **Production & Engineering Center** Brother Industries, Ltd. Tel: +81-52-824-2511(Representative) FAX: +81-52-824-5166

Laser All-in-One MFC-L5900DW


- Specifications:
- Electrophotographic Dry Process
- Business Use
- Recording Paper Size: A4 (Max. 210 x 297mm)
- Original Sheet Size: Max-width 215.9mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing
- Product weight: 15.62 kg

(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period. < Main environmental impact in the product lifecycle > • Energy consumption 4,280MJ

- Energy consumption
- Global warming impact (CO₂ equivalent)
 - Acidification impact (SO₂ equivalent)
- 237.2kg 0.351kg





- Electric power consumption in 5 years of "Use stage" is113kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

Notes

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

[Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, September 29, 2004, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School Independent verification of the label and data, according to ISO 14025 🛛 internal 🔳 external Third party verifier *: System auditor, Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type III category.

Product Environmental Information Data Sheet (PEIDS)



Unit Function DB version

rization Factor DB version

F-02As-02 Document control no Brother Industries, LTD. Product vendor EcoLeaf registration no AH-18-E220

1	PCR name	Facsimile		Product type	MFC-L5900DW				
	PCR code	AH-03	Product weight (kg)	15.62	Package (kg)	5.04	Weight total (kg)	20.65	
					-	-			

	Life Cycle Stage					Produ	uction				T
In/O	ut iter	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Total
		г		consumption	MJ	2.17E+03	2.22E+02	6.63E+01	1.80E+03	2.04E+01	4.28E+03
		-	nergy C	onsumption	Mcal	5.18E+02	5.30E+01	1.58E+01	4.30E+02	4.88E+00	1.02E+03
			> e	Coal	kq	9.61E+00	1.44E+00	1.55E-04	8.79E+00	1.23E-01	2.00E+01
			urc	Crude oil (for fuel)	kg	2.25E+01	1.75E+00	1.45E+00	1.43E+01	2.17E-01	4.02E+01
		ŝ		LNG	kg	4.16E+00	7.23E-01	2.24E-02	4.17E+00	6.34E-02	9.14E+00
			шē	Uranium content of an ore	kg	4.02E-04	9.76E-05	1.05E-08	5.15E-04	8.33E-06	1.02E-03
	E			Crude oil (for material)	kg	1.05E+01	3.45E-03	0	4.12E+00	0	1.47E+01
	otic	S		Iron content of an ore	kg	4.27E+00	0	0	1.28E+00	0	5.55E+00
	Ē	Exhaustible resources		Cu content of an ore	kg	2.70E-01	0	0	0	0	2.70E-01
	nsu			Al content of an ore	kg	1.13E-01	0	0	4.59E-02	0	1.59E-01
	۲.	esc		Ni content of an ore	kg	1.92E-02	0	0	6.53E-03	0	2.58E-02
	0	<u>ت</u>	resources	C content of an ore	kg	2.73E-02	0	0	9.28E-03	0	3.66E-02
	ũ	ļģi	no	Mn content of an ore	kg	2.25E-02	0	0	7.83E-03	0	3.03E-02
	D0	nst	se	Pb content of an ore	kg	1.28E-02	0	0	0	0	1.28E-02
	ŝ	าลเ	ц.	Sn content of an ore	kg	-	-	-	-	-	
	Impact by Resource Consumption	Ä	Mineral	Zn content of an ore	kg	1.27E-01	0	0	0	0	1.27E-01
	, p		Ain	Au content of an ore	kg	-	-	-	-	-	
	ac		~	Ag content of an ore	kg	-	-	-	-	-	4.045.00
es	du			Silica Sand	kg	1.03E+00	0	0	1.50E-02	0	1.04E+00
iys	-			Halite	kg	2.42E+00	8.79E-06	0	2.77E-01	6.33E-03	2.70E+00
nai				Limestone	kg	1.38E+00	5.70E-04	0	4.27E-01	1.73E-01	1.98E+00
/ a		Dave		Natural soda ash	kg	1.07E-01	0	0	0 8.21E+00	0	1.07E-01
LO.			ewable	Wood	kg	6.13E+00	1.13E-02			1.04E+02	1.44E+01
Inventory anaiyses		reso	urces	Water	kg	9.94E+03	1.09E+03	1.17E-01	6.45E+03		1.76E+04
Ž	Emission/Discharge to the environment			CO2	kg	1.06E+02	1.16E+01	4.71E+00	9.23E+01	1.86E+01	2.33E+02
_	E		e	Sox	kg	6.44E-02 1.43E-01	8.66E-03 7.36E-03	2.89E-03 2.28E-02	6.05E-02 9.92E-02	9.76E-03 2.08E-02	1.46E-01 2.93E-01
	ic	to Atmosphere		Nox N2O	kg	1.43E-01 1.05E-02	2.24E-04				1.53E-01
	en V			CH4	kg	1.05E-02 1.07E-03	2.24E-04 2.61E-04	7.83E-04 2.81E-08	3.75E-03 1.38E-03	2.66E-05 2.23E-05	2.73E-02
	ē			CH4 CO	kg kg	1.26E-02	1.70E-03	6.05E-03	1.63E-03	3.80E-03	4.05E-02
	ott			NMVOC	kg	2.10E-02	5.11E-04	5.49E-08	2.69E-02	4.37E-05	5.35E-02
	e			CxHy	kg	4.98E-03	6.24E-05	6.80E-04	1.82E-03	7.07E-05	7.61E-03
	arc			Dust	kg	1.48E-02	4.17E-04	2.17E-03	7.28E-03	1.18E-03	2.59E-02
	sch			BOD	kg	-	-	-	-	-	2.000-02
	ö	ਤ ਵ	in er	COD	kg	-	-	-	-	-	
	/uo	Vat	Vat	N total	kg	-	-	-	-	-	
	SSI	to Water system	to Water domain	P total	kg	-	-	-	-	-	
	E.	۳ ب	Ę U	SS	kg	-	-	-	-	-	
				Unspecified Solid Waste	ka	1.40E+00	2.40E-04	0	3.75E+00	7.91E+00	1.31E+01
	otb	to	Soil	Slag	kg	1.54E+00	0	0	3.90E-01	0	1.93E+00
	mpact by	sv	stem	Sludge	kg	1.36E-01	0	0	9.84E-02	0	2.34E-01
	<u></u>	5,		Low level radio-active waste	ka	2.82E-04	6.82E-05	7.33E-09	3.59E-04	5.82E-06	7.15E-04
ine	≥ S	Exha	ustible	Energy resources (crude oil equivalent)	kg	3.70E+01	4.34E+00	1.48E+00	2.92E+01	4.41E-01	7.24E+01
Impact assessmen	by Res			Mineral resources (Iron ore equivalent)	kg	8.62E+01	1.90E-03	0	8.97E+00	0	9.51E+01
ess	/			Global Warming (CO2 equivalent)	kg	1.09E+02	1.17E+01	4.92E+00	9.34E+01	1.86E+01	2.37E+02
ass	. io		to	Acidification (SO2 equivalent)	kg	1.64E-01	1.38E-02	1.89E-02	1.30E-01	2.43E-02	3.51E-01
ct a	ss s	Atm	ospher								
ba	ш		e								
<u> </u>	ш										

[Notes for readers: EcoLeaf common rules]

I. Stage related

A. "Production" stage is intended for two sub-stages listed below.

(1) "Raw material" production: consists of mining, transportation and raw material production

(2) "Product" production: consists of the parts processing, assembly and installation.

B. Distribution' stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage. C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).

D. "Disposition" stage is intended for environmental impacts by product disposition.

II. Inventory analyses

A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore,

B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel. C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III Impact analyses

Result of the Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO, in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere. Water and Soil system

IV Data entry format

A. Exponential notation, after the decimal point to two, should be used. B. Indicate "O" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results. C. Indicate "-" if calculation nor estimation can not be done, in order to differentiate to indicate "zero". D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data).

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

1. Product weight includes a toner cartridge, a drum unit and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.
- In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery. 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.

The transportation distance in Japan uses 100 km as average distance.

4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48,000 sheets and printing 48,000 sheets by receiving.

This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included The distribution impact of consumables is calculated under the same condition of products:


The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance. Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machin

6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan

Product data sheet





	PCR name		Facsimile(PCR ID:AH-03)		Product t	ype	MFC-L5900DW					
LC	A/LCIA in units of:		1		Product weig	luct weight (kg) 15.62 Pack		age (kg)	5.04	Weight total (kg)	20.65	
1. Pro	1. Product information (per unit): parts etc. by material and by process/assembly method											
		Breakdown of primary materials						arts, wh	ich need to	o apply Proc	cessing / Assembly Base Uni	its (Parts B, C)
	Material na	ame	Weight (kg)	Material name	Weight (kg)	P	Process name		Weigh	t (kg)	Process name	Weight (kg)
	Steel	Steel		Semiconductor substrate	1.15E+00	Press molding:Iron (kg)		lition (kg) 3.62E		E+00 I	Parts assembly (kg)	2.70E+00
	Stainless steel		1.21E-01	Medium-sized motor	5.62E-01	Press molding:Nonferrous metal (kg)		1.78	E-02			
+	Aluminum		5.99E-02	Lubricants	1.84E-02	Injec	Injection molding (kg)		1.14E	+01		
roduct	Thermoplasti	c resin	1.13E+01			Gla	ss molding	(kg)	9.34	E-01		
2 2	Thermosettin	g resin	6.22E-02									
<u>م</u>	Rubbe	r	1.63E-01									
	Glass		9.34E-01									
	Paper		2.83E+00									
	Subtota	ıl	1.89E+01	Subtotal	1.73E+00							
		Total					Subtotal		1.60E	+01	Subtotal	2.70E+00

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Energy
	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Diesel truck: 10 ton (kg.km)	LNG as fuel (kg)	Diesel oil as fuel (kg)	Heavy oil fuel (kg)	Freight by ship (kg.km)
ion	Quantity	3.66E-02	1.02E+01	7.07E+01	1.44E+01	2.07E-02	2.02E-02	4.86E-02	4.94E+02
Consumption	Note								
Insu	Classification	Material	Material	Energy	Material	Energy			
Cor	Distribution	Raw wood (foreign) (kg)	Low density polyethylene (kg)	LPG(NPG) as fuel (kg)	PP (kg)	Incineration: Industrial waste (kg)			
	Quantity	7.38E-03	1.14E-03	3.84E-02	2.32E-03	4.74E-02			
	Note								
arge	Classification								
Disch	Distribution								
Emission/	Quantity								
Emis	Note								
Note									

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)						
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
ution	Quantity	2.07E+01	7.00E+01	2.65E+01	5.45E+03	2.07E+01	3.50E+03	1.00E+02	7.23E+04
ibuti	Note								
Distrit	Means of transportation	Diesel truck: 10 ton (kg.km)							
Di	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	2.07E+01	1.00E+02	2.64E+01	7.81E+03				
	Note								
Note									

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Cold-Rolled steel plate (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)	Aluminum plate (kg)
	Quantity	1.13E+02	3.10E+03	3.29E+04	4.43E+03	3.76E-03	1.22E+00	4.11E-02	4.34E-02
	Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Low density polyethylene (kg)	PP (kg)	PS (kg)	Polycarbonate (kg)	PC-ABS(70/30)(kg)	POM(polyacetal) (kg)	ABS (kg)	AS resin (kg)
	Quantity	1.81E-01	1.90E-01	1.85E+00	6.87E-02	2.05E-02	1.93E-01	2.62E-01	1.38E+00
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	MMA resin (kg)	PET (kg)	Expandable act polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Paper (Western style)	Injection molding (kg)	Press molding: Iron (kg)
Product	Quantity	5.85E-03	9.59E-02	7.62E-02	2.75E-02	3.68E+00	5.15E-02	2.97E+00	1.26E+00
ro	Note								
_	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Parts assembly (kg)	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Diesel oil as fuel (kg)	LPG(NPG) as fuel (kg)	LNG as fuel (kg)
	Quantity	4.21E-01	1.18E+01	7.07E+01	4.96E+03	2.16E+02	1.22E-02	2.33E-02	2.07E-02
	Note		Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Process		
	Distribution	Heavy oil fuel (kg)	Low density polyethylene (kg)	PP (kg)	Raw wood (foreign) (kg)	Corrugated cardboard (kg)	Incineration: Industrial waste (kg)		
	Quantity	7.62E-01	1.79E-02	3.64E-02	7.38E-03	1.15E-01	1.76E-01		
	Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years		

Note Electric power consumption in 5 years of "Use stage" is 113.4kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

Consumables	les	Classification	Consumption	Process	Incineration to landfill (as ash) (kg)	Process		
	nab	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)		
	nsu	Quantity	1.03E+03	6.19E+00	8.65E+00	1.98E+00		
	Col	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected		

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

0	Classification	Consumption	Process	Process	Process		
nari	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to 1 andfill	Landfill: General waste (kg)		
cer	Quantity	1.88E+03	1.44E+01	1.36E+01	5.80E+00		
s	Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected		
Note							