## Product Environmental Aspects Declaration

Facsimile (PCR number: AH-03)



No. AH-18-E239 Date of publication Nov./30/2018

# brother at your side

#### http://www.brother-usa.com/

#### For inquiry:

Environmental Product Group Production Innovation Dept. Quality, Production & Engineering Center

Brother Industries, Ltd.
Tel: +81-52-824-2511(Representative)
FAX: +81-52-824-5166

### Color Inkjet All-in-One MFC-J6545DW Specifications:

- Color Inkjet Printing
- Business Use
- Recording Paper Size: LDR (Max. 17 "x 11")
- Original Sheet Size: Max-width 11.7"
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing
- Product weight: 19.62 kg


(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

< Main environmental impact in the product lifecycle >

Energy consumption 3,250MJ
 Global warming impact (CO<sub>2</sub> equivalent) 177.3kg
 Acidification impact (SO<sub>2</sub> equivalent) 0.256kg





- Electric power consumption in 5 years of "Use stage" is 91.2kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

#### Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

#### [Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, September 29, 2004, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School Independent verification of the label and data, according to ISO 14025 ☐ internal ■ external Third party verifier \*: System auditor, Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

\* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type Ⅲ category.

### Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-18-E239

Unit Function DB version rization Factor DB version

v2.1	
v2.1	

PCR name	Facsimile	Product type	MFC-J6545DW				
PCR code	AH-03	Product weight (kg)	19.62	Package (kg) 3.44		Weight total (kg)	23.06

	_			Life Cycle Stage		Produ	uction				
In/Ou	ut iter	ns			Unit	Raw material	Product	Distribution	Use	Disposition	Total
, 00	Energy Consumption					1.89E+03	3.15E+02	6.38E+01	9.54E+02	2.43E+01	3.25E+03
		E	nergy (	Consumption	MJ Mcal	4.51E+02	7.52E+01	1.52E+01	2.28E+02	5.80E+00	7.75E+02
			Se	Coal	ka	8.04E+00	2.01E+00	1.49E-04	5.17E+00	1.47E-01	1.54E+01
			onic	Crude oil (for fuel)	kg	1.66E+01	2.36E+00	1.39E+00	6.35E+00	2.58E-01	2.70E+01
			2 8	LNG	ka	3.44E+00	1.01E+00	2.15E-02	2.62E+00	7.56E-02	7.17E+00
			nerg	Uranium content of an ore	kg	2.87E-04	1.36E-04	1.01E-08	3.49E-04	9.94E-06	7.82E-04
	_		ш	Crude oil (for material)	kg	1.32E+01	1.08E-02	0	5.63E-01	0	1.38E+01
	ij			Iron content of an ore	kg	4.58E+00	0	0	3.25E-03	0	4.58E+00
	υb	es		Cu content of an ore	kg	1.90E-01	0	0	1.28E-05	0	1.90E-01
	п	21		Al content of an ore	kg	4.75E-02	0	0	0	0	4.75E-02
	Suc	SOL		Ni content of an ore	kg	1.41E-02	0	0	1.57E-03	0	1.57E-02
	ŏ	re	88	C content of an ore	kg	2.06E-02	0	0	2.13E-03	0	2.27E-02
	9	<u>e</u>	Ĕ	Mn content of an ore	kg	2.43E-02	0	0	2.71E-04	0	2.45E-02
	ŭ	stib	SO	Pb content of an ore	kg	9.00E-03	0	0	1.04E-06	0	9.00E-03
	Impact by Resource Consumption	Exhaustible resources	Mineral resources	Sn content of an ore	kg	-	-	-	-	-	0.00L 00
	Re	χ̈́	<u> </u>	Zn content of an ore	kg	8.86E-02	0	0	1.02E-05	0	8.86E-02
	5	Ή	ne	Au content of an ore	kg	0.00L-02	-	-	1.021-03	-	0.00L-02
	ㅎ		≌	Ag content of an ore	kg	_	-	_	-	-	
w	pa			Silica Sand	kg	1.22E+00	0	0	4.51E-05	0	1.22E+00
Se	Ε			Halite	kg	8.92E-01	6.82E-05	0	4.21E-04	7.25E-03	9.00E-01
aj.				Limestone	kg	1.43E+00	2.36E-03	0	3.50E-02	2.04E-01	1.67E+00
ä				Natural soda ash	kg	1.30E-01	0	0	2.30E-06	0	1.30E-01
احّا			1	Wood	kg	5.58E+00	3.07E-02	0	5.40E-01	0	6.15E+00
Inventory anaiyses			1	Water	kg	7.00E+03	1.53E+03	1.12E-01	3.96E+03	1.24E+02	1.26E+04
'er	Ħ			CO2	ka	8.71E+01	1.59E+01	4.53E+00	4.47E+01	2.19E+01	1.74E+02
≦	ner			Sox	kg	4.92E-02	1.20E-02	2.79E-03	3.28E-02	1.15E-02	1.08E-01
	Į,		9.6	Nox	kg	1.23E-01	9.91E-03	2.22E-02	3.19E-02	2.45E-02	2.11E-01
	٧		ਵੱ	N2O	kg	9.34E-03	2.45E-04	7.50E-04	7.24E-04	3.22E-05	1.11E-02
	eu		Sc	CH4	kg	7.66E-04	3.64E-04	2.70E-08	9.33E-04	2.66E-05	2.09E-03
	he		Ē	CO	kg	9.70E-03	2.38E-03	5.92E-03	6.95E-03	4.46E-03	2.94E-02
	to		to Atmosphere	NMVOC	kg	1.50E-03	7.12E-04	5.28E-08	1.83E-03	5.21E-05	4.09E-03
	ge.		5	СхНу	kg	4.39E-03	6.41E-05	6.57E-04	2.54E-04	8.30E-05	5.45E-03
	Jar			Dust	kg	1.35E-02	5.31E-04	2.11E-03	1.88E-03	1.39E-03	1.94E-02
	sch	E	Ë	BOD	kg	-	-	-	-	-	
	impact by Emission/Discharge to the environment	to Water system	o Water domain	COD	kg	-	-	-	-	-	
	io	er s	er d	N total	kg	-	-	-	-	-	
	iss	Nati	Vate	P total	kg	-		-	-	-	
	Ш	to \	to V	SS	kg	-	-	-	-	-	
	5		em	Unspecified Solid Waste	kg	8.28E-01	8.19E-04	0	4.10E-01	9.07E+00	1.03E+01
	ct		system	Slag	kg	1.55E+00	0	0	2.07E-03	0	1.56E+00
	pa		to Soil	Sludge	kg	2.66E-02	0	0	0	0	2.66E-02
	lπ		ę	Low level radio-active waste	kg	2.01E-04	9.50E-05	7.05E-09	2.43E-04	6.94E-06	5.46E-04
eu.	by Res			Energy resources (crude oil equivalent)	kg	2.83E+01	5.97E+00	1.42E+00	1.57E+01	5.25E-01	5.19E+01
ssm	요쨗		Disease	Mineral resources (Iron ore equivalent)	kg	6.59E+01	5.95E-03	0	1.56E+00	0	6.75E+01
ses	phone		еге	Global Warming (CO2 equivalent)	kg	8.97E+01	1.60E+01	4.73E+00	4.50E+01	2.20E+01	1.77E+02
t as	in the same of the		osph	Acidification (SO2 equivalent)	kg	1.35E-01	1.89E-02	1.83E-02	5.52E-02	2.87E-02	2.56E-01
mpactassessmen	Balan Das		Atm								
Ē	2		to At								
Motoc	for re	adere I	col eaf	common rules]		·	·	· · · · · · · · · · · · · · · · · · ·	·	·	·

#### Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below
- (1) "Raw material" production: consists of mining, transportation and raw material production. (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition" stage is intended for environmental impacts by product disposition.

#### II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.

  B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

#### III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO<sub>2</sub> in case of "Global Warming").

- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system

#### IV Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.
- C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

  D. Row total of the data is automatically calculated, excluding a row includes " " item. Row total of such is presented as a blank (no data).
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

#### [Notes for readers: Target product specific]

- 1. Product weight includes a toner cartridge, a drum unit and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.
- In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery. 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.
- The transportation distance in Japan uses 100 km as average distance. 4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48,000 sheets and printing 48,000 sheets by receiving.
- This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance

Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material

- This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables 5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material.
- This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines
- 6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

#### **Product data sheet**

(Input data and parameters for LCA

	(Input data and parameters for ECA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-18-E239



PCR name	Facsimile(PCR ID:AH-03)	Product type	MFC-J6545DW				
LCA/LCIA in units of:	1	Product weight (kg)	19.62	Package (kg)	3.44	Weight total (kg)	23.06

1. Product information (per unit): parts etc. by material and by process/assembly method

	Bro	eakdown of pi	imary materials		Math breakdown of parts, whi	ch need to apply	Processing / Assembly Base U	nits (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	3.97E+00	Semiconductor substrate	8.03E-01	Press molding:liton (kg)	4.05E+00	Parts assembly (kg)	1.51E+00
	Stainless steel	8.90E-02	Wood	6.13E-04	Press molding:Nonferrous metal (kg)	1.17E-02		
-	Aluminum	1.17E-02	Water	2.07E-01	Injection molding (kg)	1.37E+01		
roduct	Thermoplastic resin	1.35E+01	Medium-sized motor	3.98E-01	Glass molding (kg)	1.31E+00		
2	Thermosetting resin	5.52E-02	Lubricants	4.73E-03				
Δ.	Rubber	6.72E-02						
	Glass	1.31E+00						
	Paper	2.61E+00						
	Subtotal	2.16E+01	Subtotal	1.41E+00				
		Total		2.31E+01	Subtotal	1.90E+01	Subtotal	1.51E+00

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

	Classification	Material	Material	Energy	Energy	Energy	Material	Energy	Energy
	Distribution	Corrugated cardboard (kg)	Polypropylene (kg)	Furnace urban gas (13A) (m3)	Electricity (kWh)	Diesel truck:4 ton (kg·km)	Clean water (kg)	Gasoline as fuel (kg)	Freight by air (kg·km)
ion	Quantity	1.44E-02	1.09E-02	1.27E-03	1.71E+01	9.92E-01	5.49E+00	2.97E-04	6.10E+01
Consumption	Note								
l light	Classification	Energy	Energy	Energy	Energy	Energy	Energy	Energy	
S	Distribution	Freight by ship (kg·km)	Injection molding (kg)	Incineration: Industrial waste (kg)	Diesel oil as fuel (kg)	Diesel truck:10 ton (kg·km)	Sewage processing (kg)	Furnace LPG (kg)	
	Quantity	6.50E+02	1.09E-02	3.64E-02	1.16E-04	6.84E+01	5.48E+00	3.00E-02	
	Note								
arge	Classification								
/Disch	Distribution								
, uoi	Quantity								
Emiss	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck:20 ton (kg·km)	Freight by ship (kg·km)						
	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)
- -	Quantity	2.31E+01	1.05E+02	3.56E+01	6.80E+03	2.31E+01	3.00E+03	1.00E+02	6.92E+04
bution	Note								
Distrik	Means of transportation	Diesel truck:10 ton (kg·km)							
ă	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)				
	Quantity	2.31E+01	1.00E+02	3.55E+01	6.49E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kWh)	Diesel truck:20 ton (kg·km)	Freight by ship (kg·km)	Diesel truck:10 ton (kg·km)	Stainless steel plate (kg)	Low density polyethylene (kg)	Polypropylene (kg)	POM(polyacetal) (kg)
		, , ,		0 7 110 7					
	Quantity	9.12E+01	2.41E+02	5.43E+03	2.30E+02	9.97E-03	4.42E-02	3.52E-01	3.28E-02
	Note	Electricity consumption for 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years	Distribution of consumables used in 5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	ABS (kg)	PET (kg)	Nitrile-butadiene rubber(NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper(Western style) (kg)	Assembled circuit board (kg)	Clean water (kg)
	Quantity	1.01E-01	3.20E-04	2.64E-03	1.28E-01	1.05E-01	1.23E-02	9.28E-05	1.02E+00
Product	Note								
ĕ	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Injection molding (kg)	Press molding:lion (kg)	Parts assembly (kg)	Electricity (kWh)	Furnace urban gas (13A) (m3)	Gasoline as fuel (kg)	Diesel oil as fuel (kg)	Furnace LPG (kg)
	Quantity	5.33E-01	9.97E-03	4.42E-02	3.23E+00	6.25E-03	6.46E-05	7.56E-05	6.54E-03
	Note				Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Process	Process	
	Distribution	Freight by ship (kg·km)	Diesel truck:10 ton (kg·km)	Polypropylene (kg)	Clean water (kg)	Injection molding (kg)	Sewage processing (kg)	Incineration: Industrial waste (kg)	
	Quantity	3.21E+03	3.19E+02	5.36E-02	4.81E-01	5.36E-02	4.44E-01	9.06E-02	
	Note	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	Production of consumables used in 5 years	

Note Electric power consumption in 5 years of "Use stage" is 91.2kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

 	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	cycle iiiiciiiiaiic	c concumus.	oo ama ropiacemi	one parto		
les	Classification	Process	Process	Process	Process		
nab	Distribution	Diesel truck:4 ton (kg·km)	Shredding (kg)	Incineration to landfill(as ash) (kg)	Landfill:General waste (kg)		
nsu	Quantity	2.18E+02	1.95E+00	2.24E+00	1.51E-02		
ទ	Note	Consumables not collected	Consumables not collected	Consumables not collected	Consumables not collected		

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

0	Classification	Consumption	Process	Process	Process		
ä	Distribution	Diesel truck: 4 ton (kg·km)	Shredding (kg)	Incineration to landfill(as ash) (kg)	Landfill:General waste (kg)		
cer	Quantity	2.19E+03	1.92E+01	1.60E+01	6.58E+00		
S	Note	Machines not collected	Machines not collected	Machines not collected	Machines not collected		

Note