# Product Environmental Aspects Declaration

Facsimile (PCR number: AH-03)



No. AH-19-E250 Date of publication May./10/2019



## http://www.brother-usa.com/

For inquiry:

Environmental Promotion Group Law, Environment&General Affairs Dept.

Brother Industries, Ltd. Tel: +81-52-824-2511(Representative) FAX: +81-52-821-5177


## Laser All-in-One MFC-L6900DWG Specifications:

- Electrophotographic Dry Process
- Business Use
- Recording Paper Size: A4 (Max. 210 x 297mm)
- Original Sheet Size: Max-width 215.9mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing
- · Product weight: 19.02 kg

(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period. < Main environmental impact in the product lifecycle > • Energy consumption 5,170MJ

Energy consumption 5,170MJ
 Global warming impact (CO<sub>2</sub> equivalent) 304.0kg
 Acidification impact (SO<sub>2</sub> equivalent) 0.676kg



- · Electric power consumption in 5 years of "Use stage" is125kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

#### Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.ecoleaf-jemai.jp/eng/ for details.
- 3. Basic Units used for calculations are based on Japan domestic data at this time, due to a lack of base data to establish localized Basic Unit for overseas locations adequately.
- 4. This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

## [Supplemental environmental information]

The product assembly and main parts of toner and photoreceptor are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program.

PCR review was conducted by: PCR Deliberation Committee, September 29, 2004, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School Independent verification of the label and data, according to ISO 14025 ☐ internal ■ external Third party verifier \*: System auditor. Yasuo Koseki

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

\* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

The EcoLeaf is an environmental labeling program that belongs to the ISO-Type Ⅲ category.

## Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-19-E250

Unit Function DB version Characterization Factor DB version

v2.1	
v2.1	

PCR name	Facsimile	Product type	MFC-L6900DWG				
PCR code	AH-03	Product weight (kg)	19.02	Package (kg)	4.25	Weight total (kg)	23.27

			Life Cycle Stage	11.5	Prod	uction	Distribution .	I I s	Discounting of	Total
In/Ou	ut iten	ns		Unit	Raw material	Product	Distribution	Use	Disposition	Total
		Energy (	Consumption	MJ	2.95E+03	2.62E+02	2.36E+02	1.70E+03	2.30E+01	5.17E+03
		Lileigy	onsumption	Mcal	7.05E+02	6.26E+01	5.63E+01	4.06E+02	5.49E+00	1.23E+03
		y y	Coal	kg	1.17E+01	1.66E+00	5.53E-04	8.35E+00	1.39E-01	2.18E+01
		arg urc	Crude oil (for fuel)	kg	3.44E+01	2.15E+00	5.15E+00	1.40E+01	2.45E-01	5.60E+01
		Energy resource	LNG	kg	4.98E+00	8.33E-01	7.96E-02	4.09E+00	7.14E-02	1.00E+01
		9 2	Uranium content of an ore	kg	5.01E-04	1.12E-04	3.72E-08	5.17E-04	9.38E-06	1.14E-03
	uc		Crude oil (for material)	kg	1.22E+01	1.29E-02	0	2.21E+00	0	1.44E+01
	pţic	တ္	Iron content of an ore	kg	4.96E+00	0	0	5.32E-01	0	5.49E+00
	Ē	8	Cu content of an ore	kg	2.80E-01	0	0	0	0	2.80E-01
	Consumption	l li	Al content of an ore	kg	1.52E-01	0	0	1.13E-01	0	2.65E-01
	ò	SS SS	Ni content of an ore	kg	1.23E-02	0	0	3.50E-03	0	1.58E-02
	Эе	ustible res	C content of an ore	kg	1.81E-02	0	0	4.92E-03	0	2.30E-02
	Š	ig B	Mn content of an ore	kg	2.48E-02	0	0	3.38E-03	0	2.82E-02
	no.	rst	Pb content of an ore	kg	1.30E-02	0	0	0	0	1.30E-02
	Impact by Resource	Exhaustible resources eral resources	Sn content of an ore	kg	-	-	-	-	-	
	-R	Exha	Zn content of an ore	kg	1.28E-01	0	0	0	0	1.28E-01
	á,	≟	Au content of an ore	kg	-	-	-	-	-	
	act		Ag content of an ore	kg	-	-	-	-	-	
es	ďu		Silica Sand	kg	1.10E+00	0	0	6.22E-03	0	1.11E+00
ys	_		Halite	kg	2.52E+00	5.00E-05	0	1.77E-01	7.14E-03	2.70E+00
آھ			Limestone	kg	1.98E+00	3.24E-03	0	2.49E-01	1.93E-01	2.43E+00
ਬ			Natural soda ash	kg	1.14E-01	0	0	0	0	1.14E-01
9		Renewable	Wood	kg	2.13E+01	7.20E-02	0	4.68E+00	0	2.60E+01
Inventory anaiyses		resources	Water	kg	1.21E+04	1.26E+03	4.05E-01	6.30E+03	1.18E+02	1.98E+04
١٤	ent		CO2	kg	1.61E+02	1.38E+01	1.66E+01	8.64E+01	2.08E+01	2.99E+02
_	ű.	Ф	Sox	kg	9.17E-02	1.02E-02	2.04E-02	6.44E-02	1.09E-02	1.98E-01
	ror	ЭĒ	Nox	kg	2.49E-01	9.67E-03	2.55E-01	1.46E-01	2.32E-02	6.84E-01
	nvi	d.	N2O	kg	1.54E-02	3.37E-04	2.99E-04	3.07E-03	3.03E-05	1.91E-02
	9	ĕ	CH4	kg	1.34E-03	3.00E-04	9.98E-08	1.38E-03	2.51E-05	3.04E-03
	₽	₽tt	CO	kg	2.46E-02	2.02E-03	1.02E-01	4.02E-02	4.24E-03	1.73E-01
	to to	to Atmosphere	NMVOC	kg	2.61E-03	5.87E-04	1.96E-07	2.70E-03	4.92E-05	5.95E-03
	rge	_	СхНу	kg	7.74E-03	1.17E-04	5.15E-03	2.71E-03	7.96E-05	1.58E-02
	cha		Dust	kg	2.26E-02	6.11E-04	2.04E-02	1.11E-02	1.32E-03	5.60E-02
	Emission/Discharge to the environment	5 - 5 -	BOD	kg	-	-	-	-	-	
	n/C	system to Water domain	COD	kg	-	-	-	-	-	
	sio	N K	N total	kg	-	-	-	-	-	
	mis	o to	P total	kg	-	-	-	-	-	
			SS	kg	1.74E+00	1.19E-03		2.18E+00	- 0.025.00	1 205 .01
	by	to Soil	Unspecified Solid Waste	kg	1.74E+00 1.73E+00		0		8.93E+00	1.29E+01
	act		Slag	kg	2.12E-01	0	0	1.63E-01 2.42E-01	0	1.90E+00 4.54E-01
	mpact by	system	Sludge Low level radio-active waste	kg	3.50E-04	7.83E-05	2.61E-08	3.60E-04	6.56E-06	7.95E-04
± l		Evhauetible	Energy resources (crude oil equivalent)	ka	5.20E+01	5.13E+00	5.25E+00	2.85E+01	4.97E-01	9.14E+01
Impact assessment	by Res		Mineral resources (from one equivalent)	kg	8.41E+01	7.11E-03	0.25E+00	4.83E+00	4.97E-01 0	8.90E+01
ssn	-	resources	Global Warming (CO2 equivalent)	kg ka	1.65E+02	1.39E+01	1.67E+01	8.73E+01	2.08E+01	3.04E+02
Ses	, L	to	Acidification (SO2 equivalent)		2.66E-01	1.70E-02	1.99E-01	1.67E-01	2.72E-02	6.76E-01
as	by Emission	Atmospher	Acidincation (502 equivalent)	kg	2.00E-01	1.700-02	1.99E-01	1.07 E-01	Z.12E-02	0.70E-01
act	b Sir									
E C	Ш	е								
		aders: Ecol eaf c								

#### [Notes for readers: Ecol eaf common rules]

#### I. Stage related

- A. "Production" stage is intended for two sub-stages listed below.
- (1) "Raw material" production: consists of mining, transportation and raw material production.
- (2) "Product" production: consists of the parts processing, assembly and installation.

  B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g. replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage is intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g. replacement parts).
- D. "Disposition" stage is intended for environmental impacts by product disposition.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g. iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

#### III Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO<sub>2</sub> in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.
- B. Indicate "O" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

  C. Indicate " " if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

  D. Row total of the data is automatically calculated, excluding a row includes " " item. Row total of such is presented as a blank (no data).

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

- 1. Product weight includes the accessories as standard equipment, a toner cartridge and a drum unit. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter, polyethylene bags).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance in USA uses 2,859.7 km as Bartlett, TN to CA distance.
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48,000 sheets and printing 48,000 sheets by receiving

This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the warehouse of USA is based on actual distance. The transportation distance in USA uses 2,859.7 km as Bartlett, TN to CA distance.

Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible ma

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables

- 5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material
- This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines
- 6. Others: This declaration was produced using Product Category Rule intended for a product model sold in the Japanese market and using the qualitative and quantitative data collected in Japan.

## **Product data sheet**

Input data and parameters for I CA

	(Input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-19-E250



PCR name	Facsimile(PCR ID:AH-03)	Product type				DDWG	
LCA/LCIA in units of:	1	Product weight (kg)	19.02	Package (kg)	4.25	Weight total (kg)	23.27

1. Product information (per unit): parts etc. by material and by process/assembly method

	Br	eakdown of pi	rimary materials		Math breakdown of parts, whi	ch need to apply	Processing / Assembly Base Un	its (Parts B, C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	4.12E+00	Semiconductor substrate	1.16E+00	Press molding:līon (kg)	4.20E+00	Parts assembly (kg)	4.28E+00
	Stainless steel	7.70E-02	Medium-sized motor	6.04E-01	Press molding:Nonferrous metal (kg)	4.97E-02		
-	Aluminum	9.35E-02	Lubricants	1.78E-02	Injection molding (kg)	1.27E+01		
duct	Thermoplastic resin	1.27E+01			Glass molding (kg)	1.01E+00		
Į po	Thermosetting resin	6.53E-02						
~	Rubber	1.87E-01						
	Glass	1.01E+00						
	Paper	3.20E+00						
	Subtotal	2.15E+01	Subtotal	1.79E+00				
		Total		2.33E+01	Subtotal	1.79E+01	Subtotal	4.28E+00

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in  $SO_2,\,NO_2$  equivalent.

	Classification	Energy	Material	Energy	Material	Energy	Material	Energy	Energy
	Distribution	Diesel truck:10 ton (kg·km)	Corrugated cardboard (kg)	Diesel truck:20 ton (kg·km)	Electroplated steel Plate (kg)	Electricity (kWh)	High density polyethylene (kg)	Freight by ship (kg·km)	Diesel oil as fuel (kg)
	Quantity	5.50E+01	6.81E+00	1.79E+04	4.51E-03	2.39E+01	3.84E-03	3.14E+05	1.77E-02
	Note								
io	Classification	Energy	Energy	Material	Material	Energy	Material	Material	Energy
npt	Distribution	Heavy oil as fuel (kg)	Furnace LPG (kg)	Low density polyethylene (kg)	Raw wood(Imported) (kg)	Freight by rail (kg·km)	ABS (kg)	Polypropylene (kg)	Incineration: Industrial waste (kg)
Consumption	Quantity	1.80E-01	3.41E-02	1.63E-01	6.00E-03	1.02E+05	6.68E-02	1.00E-02	7.07E+00
Š	Note								
	Classification	Material	Material	Energy	Energy	Energy			
	Distribution	PET (kg)	Paper(Western style) (kg)	Injection molding (kg)	Press molding:lton (kg)	Landfill:lindustrial waste (kg)			
	Quantity	6.56E-04	3.25E-03	2.15E-01	4.51E-03	4.51E-03			
	Note								
arge	Classification								
Disch	Distribution								
sion	Quantity								
E	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	0	Aeans of transportation	Diesel truck:20 ton (kg·km)					
	5	Conditions	Mass(kg)	Distance (km)	Loading Ratio(%w)	Load(kg·km)		
strib	=	Quantity	2.33E+01	2.86E+03	2.47E+01	2.70E+05		
Ž		Note						

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

. I PIC		ccessories subje							
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Freight by rail (kg·km)	Cold-Rolled steel plate (kg)	Electroplated steel Plate (kg)	Stainless steel plate (kg)
	Quantity	1.25E+02	6.61E+04	5.57E+04	2.79E+03	1.90E+04	3.76E-03	5.02E-01	2.21E-02
		Electricity	Distribution of	Distribution of	Distribution of	Distribution of			
	Note	consumption for 5	consumables	consumables	consumables	consumables			
	Classification	years Consumption	used in 5 years  Consumption	used in 5 years	used in 5 years	used in 5 years  Consumption	0	Consumption	Consumption
			Low density polyethylene (kg)	Consumption	Consumption	Polycarbonate (kg)	Consumption PC-ABS(70/30)(kg)		
	Distribution	Aluminum plate (kg)		PP (kg)	PS (kg)	, (0)	1 71 07	POM(polyacetal) (kg)	ABS (kg)
	Quantity	1.07E-01	7.57E-02	6.07E-02	7.77E-01	6.53E-02	1.05E-02	9.47E-02	7.60E-02
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	MMA resin (kg)	AS resin (kg)	PET (kg)	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Paper (Western style)	Press molding: Iron (kg)
	Quantity	5.85E-03	1.02E+00	4.39E-02	3.05E-02	6.31E-02	1.72E+00	3.39E-02	5.28E-01
	Note								
헐	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	Press molding: Nonferrous metal (kg)	Injection molding (kg)	Parts assembly (kg)	Electricity (kwh)	Heavy oil fuel (kg)	Diesel oil as fuel (kg)	Gasoline as fuel (kg)	LPG(NPG) as fuel (kg)
₫	Quantity	6.34E-02	1.30E+00	1.53E-01	7.55E+00	5.55E-01	3.26E-03	1.48E-03	6.27E-03
					Production of	Production of	Production of	Production of	Production of
	Note				consumables	consumables	consumables	consumables	consumables
	Classification	0	0	0	used in 5 years	used in 5 years	used in 5 years	used in 5 years	used in 5 years
		Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Low density polyethylene (kg)	PP (kg)	Raw wood (foreign) (kg)	Corrugated cardboard (kg)	Injection molding (kg)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)
	Quantity	2.87E-02	2.69E-02	7.47E-01	9.26E-02	5.56E-02	3.58E+03	1.28E+04	1.02E+03
	Note	Production of consumables	Production of consumables	Production of consumables	Production of consumables	Production of consumables	Production of consumables	Production of consumables	Production of consumables
	14010	used in 5 years	used in 5 years	used in 5 years	used in 5 years	used in 5 years	used in 5 years	used in 5 years	used in 5 years
	Classification	Process	zzzz o youro	zzzz o youro	zzzz o youro	zzzz o youro	zzzz o youro	zzzz o youro	and and a second
	Distribution	Incineration: Industrial waste (kg)							
	Quantity	8.95E-01							
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Production of							
	Note	consumables							
		used in 5 years							

Note Electric power consumption in 5 years of "Use stage" is 125kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

4.2	4.2 Disposition/Recycle Information on consumables and replacement parts									
ď	Classification	Consumption	Process	Process	Process					
4	Distribution	Diesel truck:4 ton (kg·km)	Shredding (kg)	Incineration to landfil(as ash) (kg)	Landfill:General waste (kg)					
E	Quantity	6.01E+02	4.17E+00	5.08E+00	1.13E+00					
Ë	Note	Consumables not	Consumables not	Consumables not	Consumables not					
ن	S Note	collected	collected	collected	collected					

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

_			The charge and the	(p p	т., р. с с с с с			
ario		Classification	Consumption	Process	Process	Process		
	_	Distribution	Diesel truck:4 ton (kg·km)	Shredding (kg)	Incineration to landfill(as ash) (kg)	Landfill:General waste (kg)		
	cen	Quantity	2.11E+03	1.75E+01	1.52E+01	6.58E+00		
	Sc	Note	Machines not	Machines not	Machines not	Machines not		
			collected	collected	collected	collected		

Note