Product Environmental Aspects Declaration

Facsimile (PCR number: AH-03)



No. AH-10-102 Date of publication Aug./31/2010

brothe at your side

http://www.brother.co.jp/

For inquiry: Product Environmental Group Environmental Management Dept. Brother Industries, Ltd. Tel: +81-52-824-2735 FAX: +81-52-824-5667



Inkjet Multi-Function Center MFC-J615N **Specifications:**


- Color Inkjet Printing
- Personal Use
- Recording Paper Size: A4 (Max. 210 x 297mm)
- Original Sheet Size: Max-width 210mm
- Modem Speed: 33,600 bps (Automatic Switchover)
- Product Weight: 7.9 kg

(Including accessories, not including packaging and printed matter)

The following data is calculated by assuming the product sends and receives both 900 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
 - Energy consumption
 - Global warming impact (CO2 equivalent) 128kg Acidification impact (SO2 equivalent)
 - 0.174kg

2,380MJ



- · Electric power consumption in 5 years of "Use stage" is 124kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

Notes:

1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.

- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

[Supplemental environmental information]

The product assembly and main parts of ink and inkjet head are produced at plants certified with ISO 14001. The product conforms to the International Energy Star Program and the Law on Promoting Green Purchasing in Japan. The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, January 01, 2008, Name of representative: Hisashi Ishitani, KEIO University Independent verification of the label and data, according to ISO 14025:2006 🗌 internal 🔳 external Third party verifier *: Kazuo Naitou Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

* In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

Product Environmental Information Data Sheet (PEIDS)



Doc	ument	contro	l no.		F-02	2As-02		1		製品 制 http://ww	景境情報 w.jemai.or.jp
Р	roduct	vendo	or	Bro	ther In	dustries,LTD.		11	t Function DB versio		
EcoL	eaf reg	istratio	on no.		AH-	10-102			tion Factor DB versio		2.1 2.1
								Gharacteriza		··· V	2.1
	PCR	name		Face	simile Product type				MFC-J615N		
	PCR	code		AH-03		Product weight (kg)	7.87	Package (kg)	2.07	Weight total (kg)	9.94
In/Out	items			Life Cycle Stage	Unit	Produ		Distribution	Use	Disposal	Total
iii/Out	litems				MJ	Raw material 1.07E+03	Product 1.03E+02	2.29E+01	1.18E+03	9.32E+00	2.38E+03
		Energ	y Cons	umption	Mcal	2.55E+02	2.46E+01	5.47E+00	2.82E+02	2.23E+00	5.69E+02
			ly ces	Coal	kg	5.24E+00	6.61E-01	5.35E-05	6.68E+00	5.56E-02	1.26E+01
			Energy resources	Crude oil (for fuel)	kg	1.11E+01	8.33E-01	5.00E-01	7.63E+00	1.00E-01	2.02E+01
			Er esc	LNG Uranium content of an ore	kg kg	2.25E+00 2.34E-04	3.32E-01 4.47E-05	7.72E-03 3.62E-09	3.34E+00 4.52E-04	2.86E-02 3.75E-06	5.96E+00 7.34E-04
				Crude oil (for material)	kg	4.27E+00	1.79E-03	0	9.31E-02	0	4.36E+00
	ion			Iron content of an ore	kg	2.16E+00	0	0	1.71E-03	0	2.16E+00
	npt	Sec		Cu content of an ore	kg	1.77E-01	0	0	0	0	1.77E-01
	Insi	ourc		Al content of an ore	kg	3.84E-02	0	0	0	0	3.84E-02
	Lo Lo	e resources	Exnaustible reso	Ni content of an ore	kg	9.21E-03	0	0	8.31E-04	0	1.00E-02
	e O			Cr content of an ore	kg	1.31E-02 1.78E-02	0	0	1.13E-03 1.43E-04	0	1.42E-02 1.80E-02
	nuc	stib	sor	Mn content of an ore Pb content of an ore	kg kg	8.68E-03	0	0	0	0	8.68E-03
	esc	Exhaustible	rea	Sn content of an ore	kg	-	-	-	-	-	0.002-03
	R		era	Zn content of an ore	kg	8.55E-02	0	0	0	0	8.55E-02
	Impact by Resource Consumption		di	Au content of an ore	kg	-	-	-	-	-	
			~	Ag content of an ore	kg	-	-	-	-	-	
S	<u>=</u>			Silica Sand	kg	6.73E-01	0	0	1.10E-05	0	6.73E-01
Inventory anaiyses				Halite	kg	6.33E-01	1.34E-03	0	1.47E-04	3.49E-03	6.38E-01
ai)				Limestone Natural soda ash	kg kg	7.47E-01 7.09E-02	8.70E-02 0	0	1.08E-02 0	7.54E-02 0	9.20E-01 7.09E-02
an		Rene	wable	Wood	kg	4.50E+00	1.62E-02	0	7.16E-02	0	4.59E+00
Σıο		resou		Water	kg	5.99E+03	5.04E+02	4.04E-02	5.07E+03	4.69E+01	1.16E+04
ente				CO2	kg	5.61E+01	7.38E+00	1.63E+00	5.27E+01	8.15E+00	1.26E+02
Ň				SOx	kg	3.41E-02	4.99E-03	9.52E-04	4.00E-02	4.28E-03	8.43E-02
_				NOx	kg	7.26E-02	6.08E-03	7.08E-03	3.27E-02	9.23E-03	1.28E-01
	m	to	0	N2O	kg	5.02E-03	9.23E-05	2.82E-04	6.14E-04	1.26E-05	6.02E-03
	arge			CH4 CO	kg kg	6.26E-04 6.55E-03	1.20E-04 1.05E-03	9.69E-09 1.72E-03	1.21E-03 7.82E-03	1.01E-05 1.72E-03	1.96E-03 1.88E-02
	t che			NMVOC	kg	1.22E-03	2.34E-04	1.90E-08	2.36E-03	1.97E-05	3.84E-02
	t by Emission/Discl to the environment			СхНу	kg	2.33E-03	3.33E-05	2.22E-04	1.49E-04	3.42E-05	2.77E-03
	/uo			Dust	kg	7.14E-03	1.74E-04	6.92E-04	1.79E-03	5.29E-04	1.03E-02
	SSI			BOD	kg	-	-	-	-	-	
	er mi	to	0	COD	kg	-	-	-	-	-	
	t∓ S		domain	N total	kg	-	-	-	-	-	
	mpact by Emission/Discharge to the environment			P total SS	kg kg	-	-	-	-	-	
	bgn			Unspecified Solid Waste	kg	4.08E-01	- 3.26E-04	0	- 8.02E-02	4.36E+00	4.85E+00
	-			Slag	kg	8.13E-01	0	0	1.08E-03	0	8.14E-01
		to		Sludge	kg	9.65E-03	0	0	0	0	9.65E-03
		5011 S <u>)</u>	ystem	Low level radio-active waste	kg	1.64E-04	3.12E-05	2.53E-09	3.15E-04	2.62E-06	5.13E-04
	by Resource Consumption	Exhau	ustible	Energy resources (crude oil equivalent)	kg	1.91E+01	2.02E+00	5.09E-01	1.96E+01	2.01E-01	4.15E+01
+	by Ree Consui	resou	urces	Mineral resources (Iron ore equivalent)	kg	5.22E+01	9.86E-04	0	7.08E-01	0	5.29E+01
smen	rge			Global Warming (CO2 equivalent)	kg	5.74E+01	7.40E+00	1.70E+00	5.29E+01	8.15E+00	1.28E+02
asses	n/Discha	te	-	Acidification (SO2 equivalent)	kg	8.49E-02	9.25E-03	5.91E-03	6.29E-02	1.07E-02	1.74E-01
Impact assessment	t by Emission/Discharge to the environment	Atmos	sphere								
_	Impact by E to the										
	E	to Water s									

[Notes for readers: EcoLeaf common rules]

Stage related

A. "Production" stage is intended for two sub-stages listed below.

 (1) "Raw material" production: consists of mining, transportation and raw material production.
 (2) "Product" production: consists of the parts processing, assembly and installation.
 B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage. C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts)

D. "Disposal" stage in intended for environmental impacts by product disposal.

II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.
- B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel. C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CO2 in case of "Global Warming"). A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

IV. Data entry form

- Exponential notation, after the decimal point to two, should be used.
- B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

C. Indicate "--" if calculation nor estimation can not be done, in order to differentiate to indicate "zero". D. Row total of the data is automatically calculated, excluding a row includes "--" item. Row total of such is presented as a blank (no data)

(BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.)

[Notes for readers: Target product specific]

- 1. Product weight includes a handset as standard equipment, an ink cartridge and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).
- 2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of an ink cartridge and an inkjet head, as well as the impact of product assembly. In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery.
- Bistribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance
 Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 900 sheets and printing 900 sheets by receiving.

This number is calculated by supposing a user use a machine for 5 years, sending 15 sheets a month, receiving 15 a month. It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used. The production, distribution, and disposal/recycle impact of the ink cartridges used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products: The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance Since we have not collected consumables as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables. 5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material

This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

Product data sheet

	(Input data and parameters for LCA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-10-102



PSC name	Facsimile(PCR ID:AH-03)	Product type					
LCA/LCIA in units of:	1	Product weight (kg)	7.87	Package (kg)	2.07	weight total (kg)	9.94

1. Product information (per unit): parts etc. by material and by process/assembly method

		Breakdown of pri	imary materials	Math breakdown of parts, which need to apply Processing / Assembly base Units (Parts B,C)				
		•						
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	1.66E+00	Paper	2.04E+00	Press molding: Iron (kg)	1.71E+00	Parts assembly (kg)	4.02E+00
#	Stainless steel 5.81E-02		Semiconductor substrate	7.28E-01	Press molding: Nonferrous metal (kg)	4.26E-03		
duct	Aluminum	Aluminum 4.26E-03		6.50E-04	injection molding (kg)	4.39E+00		
ĕ	Other metal 0.00E+00		Medium-sized motor	3.85E-01	Glass molding (kg)	6.29E-01		
ā	Thermoplastic resin	4.15E+00	Batteries	1.40E-02				
	Thermosetting resin	9.25E-04	Lubricants	8.40E-04				
	Rubber	2.39E-01	Clean water	3.70E-02				
	Glass	6.30E-01						
	Subtotal	6.74E+00	Subtotal	3.20E+00				
	Total				Subtotal	6.73E+00	Subtotal	4.02E+00

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO₂, NO₂ equivalent.

	Classificatior	Material	Material	Energy	Energy	Energy	Material	Material	Energy
L.	Distribution	Corrugated cardboard (kg)	PP (kg)	Clean water (kg)	Furnace urban gas (13A) (m3)	Electricity (kwh)	Incineration: Industrial waste (kg)	Clean water (kg)	Incineration: Industrial waste (kg)
ption	Quantity	7.60E-03	1.80E-03	2.00E-01	2.18E-04	4.23E+00	1.17E+00	1.16E+00	1.76E-01
du	Note								
Ins	Classificatior	Energy	Energy	Energy	Energy	Energy	Energy		
Con	Distribution	Gasoline as fuel (kg)	Freight by air (kg.km)	Freight by ship (kg.km)	Heavy oil fuel (kg)	Diesel truck: 10 ton (kg.km)	Diesel truck: 4 ton (kg.km)		
	Quantity	2.60E-02	7.72E+01	1.28E+02	1.59E-03	6.47E+00	2.06E+00		
	Note								
-/ e	Classificatior								
Emission Discharge	Distribution								
iso	Quantity								
шΟ	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of transportation	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Freight by	Freight by	Freight by ship (kg.km)			
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	ship (kg.km) Distance (km)	ship (kg.km) Loading Ratio (%w)	Load (kg·km)
ion	Quantity	9.94E+00	8.50E+01	5.63E+01	1.50E+03	9.94E+00	2.63E+03	1.00E+02	2.61E+04
of I	Note								
tri	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:				
is	transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)				
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	9.94E+00	1.00E+02	4.50E+01	2.21E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classificatior	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Classification	Consumption					Consumption		Consumption
	Distribution	Electricity (kwh)	Diesel truck:	Freight by	Diesel truck:	Stainless steel	PP (kg)	POM(polyacetal)	ABS (kg)
	Distribution	Eleotholty (kill)	20 ton (kg.km)	ship (kg.km)	10 ton (kg.km)	plate (kg)	(Ng)	(kg)	ABO (Ng)
	Quantity	1.24E+02	8.96E+00	1.25E+03	2.64E+01	5.26E-03	6.23E-02	2.19E-03	2.31E-02
		Electricity	Distribution of	Distribution of	Distribution of				
	Note	consumption	consumables used in	consumables used in	consumables used in				
		for 5 years	5 years	5 years	5 years				
	Classificatior	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	PET (kg)	Nitrile-butadiene	Paper	Corrugated		injection	Press molding:	Diesel oil as
t			rubber		cardboard (kg)	Clean water (kg)		• • • •	
n p			(NBR) (kg)	(Western style)	caluboald (kg)		molding (kg)	Iron (kg)	fuel (kg)
Product	Quantity	9.93E-03	1.88E-03	1.46E-03	3.20E-02	4.98E-02	9.94E-02	5.26E-03	5.30E-05
ā									Production of
	Note								consumables used in
									5 years
	Classificatior	Consumption	Consumption	Consumption	Consumption	Process			
		LPG(NPG) as	Furnace urban	-		Incineration:			
	Distribution	fuel (kg)	gas (13A) (m3)	Electricity (kwh)	Clean water (kg)	Industrial waste (kg)			
	Quantity	3.05E-04	1.09E-04	1.57E-01	1.00E-01	8.80E-02			
		Production of							
	Note	consumables used in							
		5 years			1				

Note At "Use Stage", the product electricity consumption in 5 years usage period is 124 kWh .

4.2 Disposition/Recycle information on consumables and replacement parts

se	Classificatior	Consumption	Process	Process	Process		
q	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:		
ma		4 ton (kg.km)		landfill	General waste (kg)		
n s	Quantity	3.77E+01	2.70E-01	3.74E-01	1.58E-02		
ü	Note	Consumables not	Consumables not	Consumables not	Consumables not		
Ŭ	NOLE	collected	collected	collected	collected		
Note							

5. Disposition/Recycle stage information (per product): process method and scenarios

	Classificatior	Consumption	Process	Process	Process		
<u>.</u>	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:		
Jar	DISTIDUTION	4 ton (kg.km)		landfill (as ash) (kg)	General waste (kg)		
e	Quantity	9.08E+02	7.65E+00	5.94E+00	3.44E+00		
Ň	Note	Machines not	Machines not	Machines not	Machines not		
	Note	collected	collected	collected	collected		
Note							

1400