# **Product Environmental Aspects Declaration**

Facsimile (PCR number: AH-03)



No. AH-11-113 Date of publication May/17/2011



# http://www.brother.co.jp/

For inquiry:

Product Environmental Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2735 FAX: +81-52-824-5667




# Laser Multi-Function Center MFC-7460DN **Specifications:**

- · Electrophotographic Dry Process
- Business Use
- Recording Paper Size: A4 (Max. 210 x 297mm)
- · Original Sheet Size: Max-width 216mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 4,100MJ Global warming impact (CO<sub>2</sub> equivalent) 229kg Acidification impact (SO<sub>2</sub> equivalent) 0.347kg



- Electric power consumption in 5 years of "Use stage" is 125kWh.
- · The above data does not include the environmental impact of the paper that is used for printing.

## Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf\_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

# [Supplemental environmental information]

The product assembly and main parts of toner and photoconductor are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, February 01, 2011, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025:2006 ☐ internal ■ external Third party verifier \*: Shozo Nakamuta Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

<sup>\*</sup> In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

# Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02		製品環境情報 http://www.jemal.or.jp
Product vendor	Brother Industries,LTD.	Unit Function DB version	v2.1
EcoLeaf registration no.	AH-11-113		
		Characterization Factor DB version	v2.1

PCR name	Facsimile	Product type	MFC-7460DN				
PCR code	AH-03	Product weight (kg)	11.6	Package (kg)	2.87	Weight total (kg)	14.5

NOUNT   Filter   Fi	Life Cycle Stage				Life Cycle Stage	11	Produ	ıction	Bistoll of the		Diameter.	T. ( )
Section   Color   Co	In/Out						Raw material	Product	Distribution	Use	Disposal	Total
Section   Sect					umntion							
Section   Sect			Lileig									
Section   Sect				ses								
Section   Sect				erg								
Section   Sect				En								
Part				re								
Section   Sect												
Authority of an ore   kg   -   -   -   -   -   -   -   -   -			(O									
Authority of an ore   kg   -   -   -   -   -   -   -   -   -			ces									
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		8	'n									
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		Jn c	esc	v								
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		esi	9	92								
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		Z E	Ę	no								
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		t by	sn	sez			1.04E-02		0	6.86E-05		1.05E-02
Authority of an ore   kg   -   -   -   -   -   -   -   -   -		Cog	cha	<u>=</u>			-		-	-		
Renewable   Rene		l d	ш	neı			1.03E-01		0	6.74E-04	0	1.03E-01
Silica Sand   Kg   7.94E-01   0   0   4.16E-02   0   8.35E-01		_		≅			-		-	-	-	
Hallite   Kg							-		-			0.055.01
Limestone   kg   9.82E-01   7.10E-03   0   8.84E-01   1.21E-01   1.99E+00												
Note	ě											
Note	. <u>~</u>											
Note	<u>e</u>		D									
Note	ο >											
Note	Ď	_	110									
Note	e											
Note	Ž											
The last of the	_											
Almosphere   CO   kg   1.09E-02   1.15E-03   3.68E-03   2.21E-02   2.66E-03   4.05E-02   NMVOC   kg   1.82E-03   3.26E-04   4.24E-08   3.20E-03   3.07E-05   5.37E-03   3.26E-04   4.24E-08   3.20E-03   3.07E-05   5.37E-03   4.90E-05   4.90E-05   4.90E-04   2.16E-03   4.98E-05   6.51E-03   0.55E-03   0.55E-03   0.55E-03   0.237E-02   0.237E-0			to	0								
Water domain   Protain   Right   Protain   Right   R		ge	Atmosphere									
Water domain   Protain   Right   Protain   Right   R		har										
Water domain   Protain   Right   Protain   Right   R		scl										
Water domain   Protain   Right   Protain   Right   R		m /Di										
Water domain   Protain   Right   Protain   Right   R		lo o						2.55E-04	1.52E-03	9.55E-03	8.28E-04	2.37E-02
Water domain   Protain   Right   Protain   Right   R		iss ivi						-	-	-	-	
Water domain   Protain   Right   Protain   Right   R		E ii	to	0						-		
SS   kg   -   -   -   -   -   -   -   -   -		the the	Water of	domain						-		
to Soil system to Soil system Low level radio-active waste resources (Iron ore equivalent) kg 1.09E+01 0 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00		t p					-	-		-	-	
to Soil system to Soil system Low level radio-active waste resources (Iron ore equivalent) kg 1.09E+01 0 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00		bac					7.005.04	- 0.005.00		- 0.075 .00		1.075 .04
to Soil system to Soil system Low level radio-active waste resources (Iron ore equivalent) kg 1.09E+01 0 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00 0 2.17E+00 0 0 1.08E+00		<u>E</u>										
Soil system			+,	2								
Low level radio-active waste kg 2.45E-04 4.35E-05 5.66E-09 4.28E-04 4.09E-06 7.20E-04    Comparison of the property of the pro					Siuage	кд	3.31E-01	U	U	9.12E-01	U	1.24E+00
Exhaustible resources (crude oil equivalent) kg 2.95E+01 2.82E+00 1.14E+00 3.65E+01 3.10E-01 7.02E+01 4.14E+00 3.65E+01 4.14E+00 3.14E+00			3011 3	ystem		kg	2.45E-04	4.35E-05	5.66E-09	4.28E-04	4.09E-06	7.20E-04
D E (Marie Calantary)		source	Exhau	ıstible		kg	2.95E+01	2.82E+00	1.14E+00	3.65E+01	3.10E-01	7.02E+01
Registration of the control of the c	nent	by Res Consu	resou	urces		kg	6.12E+01	6.19E-03	0	1.77E+01	0	7.89E+01
Atmosphere Acidification (SO2 equivalent) kg 1.35E-01 9.26E-03 1.29E-02 1.73E-01 1.70E-02 3.47E-01	Impac	ct by Discharge ironment	to	0		kg	8.74E+01	7.75E+00	3.80E+00	1.17E+02	1.30E+01	2.28E+02
		Impa Emission/I to the env	Atmos	phere		kg	1.35E-01	9.26E-03	1.29E-02	1.73E-01	1.70E-02	3.47E-01

[Notes for readers: EcoLeaf common rules]

- A. "Production" stage is intended for two sub-stages listed below
- (1) "Raw material" production: consists of mining, transportation and raw material production.
  (2) "Product" production: consists of the parts processing, assembly and installation.
  B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage.
  C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal.

## II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.

  B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.

  C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CQ in case of "Global Warming").

A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.

B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

# IV. Data entry format

- A. Exponential notation, after the decimal point to two, should be used.
- R. Exponential invalent, after the electional point to troy, should be used.

  B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

  C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

  D. Row total of the data is automatically calculated, excluding a row includes "—" item. Row total of such is presented as a blank (no data).
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.

## [Notes for readers: Target product specific]

- 1. Product weight includes a toner cartridge, a drum unit and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

  2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.
- In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery.
- 3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.

4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48000 sheets and printing 48000 sheets by receiving.

This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included.

The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance

Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

# Product data sheet

(Input data and parameters for LCA

	(input data and parameters for ECA)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-11-113



PSC name	Facsimile(PCR ID:AH-03)	Product type			MFC-7460DN		
LCA/LCIA in units of:	1	Product weight (kg)	11.6	Package (kg)	2.87	weight total	14.5

1. Product information (per unit): parts etc. by material and by process/assembly method

		rimary materials		Math breakd				
		Dicardowii oi pi	inary materials		which need to app	oly Processing /	Assembly base Units (Parts	B,C)
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)
	Steel	2.35E+00	Paper	2.26E+00	Press molding: Iron (kg)	2.42E+00	Parts assembly (kg)	2.15E+00
#	Stainless steel	6.16E-02	Semiconductor substrate	9.29E-01	Press molding: Nonferrous metal (kg)	1.03E-01		
Ĕ	Aluminum	1.46E-01	Wood	0	Injection molding (kg)	7.67E+00		
ĕ	Other metal	9.40E-04	Medium-sized motor	3.35E-01	Glass molding (kg)	7.14E-01		
_	Thermoplastic resin	7.38E+00	Lubricants	8.07E-04				
	Thermosetting resin	5.20E-02	Water	0				
	Rubber	2.66E-01						
	Glass	7.14E-01						
	Subtotal	1.10E+01	Subtotal	3.53E+00				
		Total		1.45E+01	Subtotal	1.09E+01	Subtotal	2.15E+00
Moto								

Note

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in SO<sub>2</sub>, NO<sub>2</sub> equivalent.

	Classification	Material	Energy	Energy	Energy	Energy	Energy	Energy	Material
<u> </u>	Distribution	Corrugated cardboard (kg)	Electricity (kwh)	Diesel truck: 2 ton (kg.km)	Incineration: Industrial waste (kg)	LNG as fuel (kg)	Diesel oil as fuel (kg)	Freight by ship (kg.km)	PP (kg)
읉	Quantity	9.82E-02	5.02E+00	2.53E+01	1.10E-01	1.36E-02	2.49E-02	2.88E+02	1.13E-02
mption	Note								
ng.	Classification	Energy	Energy	Energy	Energy				
Con	Distribution	Heavy oil fuel (kg)	Diesel truck: 20 ton (kg.km)	Diesel truck: 10 ton (kg.km)	LPG(NPG) as fuel (kg)				
	Quantity	1.53E-03	1.52E+01	1.82E+01	2.47E-02				
	Note								
- e	Classification								
Emission Discharge	Distribution								
in is	Quantity								
шО	Note					_			

VInte

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:	Freight by	Freight by	Freight by	Freight by
	transportation	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)
_	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
.5	Quantity	1.45E+01	5.00E+01	2.80E+01	2.59E+03	1.45E+01	4.06E+03	1.00E+02	5.89E+04
p t	Note								
<b>.</b>	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:				
Dis	transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)				
	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
	Quantity	1.45E+01	1.00E+02	2.80E+01	5.19E+03				
	Note								

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption		Consumption	Consumption	Consumption
	B1 - 11 - 1	Diesel truck:	Freight by	Diesel truck:	Diesel truck:		Electroplated	Stainless	Copper
	Distribution	20 ton (kg.km)	ship (kg.km)	10 ton (kg.km)	2 ton (kg.km)		steel Plate (kg)	steel plate (kg)	plate (kg)
	Quantity	1.88E+03	3.57E+04	6.26E+03	1.52E+02		3.38E+00	7.70E-02	2.80E-03
	,	Distribution of	Distribution of	Distribution of	Distribution of				
	Note	consumables used in	consumables used in	consumables used in					
		5 years	5 years	5 years	consumables				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Aluminum plate (kg)	Low density polyethylene (kg)	PP (kg)	PS (kg)	Polycarbonate (kg)	POM(polyacetal) (kg)	AS resin (kg)	ABS (kg)
	Quantity	4.02E-01	6.77E-02	1.12E-01	2.63E+00	1.27E-01	4.30E-01	9.75E-01	3.47E-01
	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
Product	Distribution	PET (kg)	Expandable soft polyurethane (for automobile) (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	injection molding (kg)	Press molding: Iron (kg)
5	Quantity	4.37E-02	6.81E-02	6.63E-01	2.87E+00	1.52E+00	1.79E-01	4.47E+00	3.45E+00
•	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Nonferrous metal	Parts assembly (kg)	Electricity (kwh)	Gasoline as fuel (kg)	Kerosene as fuel (kg)	Heavy oil fuel (kg)	LNG (kg)	Electricity (kwh)
	Quantity	2.73E-01	2.81E+00	1.25E+02	9.80E-06	9.38E-04	6.70E-02	4.10E-02	1.69E+01
				Electricity	Production of	Production of	Production of	Production of	Production of
	Note			consumption for			consumables used in		
				5 years	5 years	5 years	5 years	5 years	5 years
	Classification	Process							
	Distribution	Incineration: Industrial waste (kg)							
	Quantity	3.44E-01							
	Note	Packaging materials for distribution of ingredient							

Note 1. Electric power consumption in 5 years of "Use stage" is 125kWh. 2. Production of consumables by China.

4.2 Disposition/Recycle information on consumables and replacement parts

4.21	JISP	osition/Recy	cie information on	consumables and	replacement parts			
5	3	Classification	Consumption	Process	Process	Process		
3	5	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:		
па	5		4 ton (kg.km)	Silledding (kg)	landfill	General waste (kg)		
1	3	Quantity	8.52E+02	8.80E+00	9.43E+00	4.28E+00		
2	Ś	Note	Consumables not					
C	5	Note	collected					

Note

5. Disposition/Recycle stage information (per product): process method and scenarios

	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		(рег р. сапасту. р. с				
	Classification	Consumption	Process	Process	Process		
ario	Distribution	Diesel truck: 4 ton (kg.km)	Shredding (kg)	Incineration to landfill	Landfill: General waste (kg)		
ق ا	Quantity	1.32E+03	1.08E+01	9.50E+00	4.12E+00		
Ű.	Note	Machines not collected					

Note