# **Product Environmental Aspects Declaration**

Facsimile (PCR number: AH-03)



No. AH-11-114 Date of publication May/17/2011



#### http://www.brother.co.jp/

For inquiry:

Product Environmental Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2735 FAX: +81-52-824-5667




## A3 Color Multi-Function Center MFC-J6710CDW **Specifications:**

- · Color Inkjet Printing
- Business Use
- Recording Paper Size: A3 (Max. 297 x 420mm)
- Original Sheet Size: Max-width 297mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 4,020MJ
- Global warming impact (CO<sub>2</sub> equivalent)
- 222kg
- Acidification impact (SO<sub>2</sub> equivalent) 0.313kg



- Electric power consumption in 5 years of "Use stage" is 170kWh.
- · The above data does not include the environmental impact of the paper that is used for printing.

#### Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf\_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

### [Supplemental environmental information]

The product assembly and main parts of ink and inkjet head are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, February 01, 2011, Name of representative: Yohji Uchiyama, University of Tsukuba, Graduate School

<sup>\*</sup> In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

#### Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-11-114

Unit Function DB version Characterization Factor DB version v2.1

PCR name	Facsimile	Product type	MFC-J6710CDW				
PCR code	AH-03	Product weight (kg)	17.6	Package (kg)	5.43	Weight total (kg)	23.0

Life Cycle Stage				Life Cycle Stage		Produ	ıction				
In/Ou	t items		_		Unit	Raw material	Product	Distribution	Use	Disposal	Total
		F	6		MJ	1.86E+03	2.21E+02	5.68E+01	1.86E+03	2.49E+01	4.02E+03
		Energ	y Cons	umption	Mcal	4.44E+02	5.27E+01	1.36E+01	4.44E+02	5.94E+00	9.60E+02
			/ es	Coal	kg	7.62E+00	1.44E+00	1.33E-04	9.62E+00	1.51E-01	1.88E+01
			60.0	Crude oil (for fuel)	kg	1.80E+01	1.76E+00	1.24E+00	1.24E+01	2.63E-01	3.37E+01
			Energy	LNG	kg	3.46E+00	7.24E-01	1.92E-02	5.19E+00	7.77E-02	9.48E+00
			Б	Uranium content of an ore	kg	2.98E-04	9.77E-05	9.00E-09	6.50E-04	1.02E-05	1.06E-03
				Crude oil (for material)	kg	1.13E+01	2.12E-03	0	2.14E+00	0	1.35E+01
				Iron content of an ore	kg	3.84E+00	0	0	5.01E-03	0	3.84E+00
		Exhaustible resources		Cu content of an ore	kg	1.86E-01	0	0	0	0	1.86E-01
	e e	o n		Al content of an ore	kg	3.53E-02	0	0	0	0	3.53E-02
	Impact by Resource Consumption	SOI		Ni content of an ore	kg	8.81E-03	0	0	2.43E-03	0	1.12E-02
	act by Resou Consumption	<u>e</u>	resources	Cr content of an ore	kg	1.31E-02	0	0	3.29E-03	0	1.64E-02
	Remp	ple	Ĭ	Mn content of an ore	kg	3.70E-02	0	0	4.18E-04	0	3.74E-02
	by	ısti	SSC	Pb content of an ore	kg	1.06E-02	0	0	0	0	1.06E-02
	g ct	าลเ		Sn content of an ore	kg	-		-	-	-	
	o pa	立	Mineral	Zn content of an ore	kg	1.04E-01	0	0	0	0	1.04E-01
	<u> </u>		َ≟ِ	Au content of an ore	kg	-		-	-	-	
			2	Ag content of an ore	kg	-	-	-	-	-	
				Silica Sand	kg	1.23E+00	0	0	3.23E-05	0	1.23E+00
တ္ဆ				Halite	kg	7.85E-01	1.45E-03	0	4.91E-03	6.79E-03	7.99E-01
-Se				Limestone	kg	1.27E+00	9.37E-02	0	3.29E-01	2.14E-01	1.91E+00
Inventory anaiyses				Natural soda ash	kg	1.32E-01	0.072 02	0	0	0	1.32E-01
a		Rene	wable	Wood	kg	1.15E+01	3.24E-02	0	2.05E+00	0	1.36E+01
			urces	Water	kg	7.65E+03	1.10E+03	1.00E-01	7.60E+03	1.28E+02	1.65E+04
윧				CO2	kg	8.86E+01	1.38E+01	4.03E+00	8.94E+01	2.30E+01	2.19E+02
ē				SOx	kg	4.89E-02	9.74E-03	2.53E-03	6.38E-02	1.20E-02	1.37E-01
_⊆				NOx	kg	1.26E-01	1.02E-02	2.05E-02	6.92E-02	2.55E-02	2.52E-01
				N2O	kg	9.02E-03	1.79E-04	6.58E-04	1.61E-03	3.21E-05	1.15E-02
			0	CH4	kg	7.97E-04	2.61E-04	2.41E-08	1.74E-03	2.74E-05	2.82E-03
	rge	Atmos	sphere	CO	kg	9.64E-03	1.98E-03	5.61E-03	1.33E-02	4.61E-03	3.51E-02
	ha	Atmosphe to the environment to the environment to domain		NMVOC	kg	9.64E-03 1.56E-03	5.11E-04	4.71E-08	3.40E-03	5.36E-05	5.53E-03
	t by Emission/Disc to the environment			CxHy	kg	4.22E-03	5.98E-05	5.97E-04	5.99E-04	8.32E-05	5.56E-03
	Q ii			Dust	kg	1.26E-02	3.73E-04	1.93E-03	3.66E-03	1.45E-03	2.00E-02
	ror			BOD	kg	1.20E-02	3.73⊑-04	1.93E-03	3.00E-U3 -	1.45E-05	2.00E-02
	iss			COD		-	-	-	-	-	
	E III	to W	/ater	N total	kg kg	-	-	-	-	-	
	the la	don	nain	P total		-	-	-	-	-	
	t 6			SS	kg	-	-	-		-	
	pac				kg	9.92E-01	5.44E-04	0	- C FCF 04	8.50E+00	1.01E+01
	<u>E</u>			Unspecified Solid Waste	kg	1.39E+00		0	6.56E-01		1.39E+00
			0	Slag	kg		0		3.14E-03	0	
			ystem	Sludge	kg	7.76E-03	U	0	0	U	7.76E-03
		3011 8	ystem	Low level radio-active waste	kg	2.09E-04	6.82E-05	6.29E-09	4.53E-04	7.14E-06	7.37E-04
	by Resource Consumption		ustible	Energy resources (crude oil equivalent)	kg	2.95E+01	4.36E+00	1.26E+00	3.02E+01	5.37E-01	6.58E+01
act ment			urces	Mineral resources (Iron ore equivalent)	kg	6.31E+01	1.17E-03	0	3.10E+00	0	6.62E+01
Impact assessment	Impact by Emission/Discharge to the environment	t	0	Global Warming (CO2 equivalent)	kg	9.10E+01	1.38E+01	4.21E+00	8.99E+01	2.30E+01	2.22E+02
	Impa Emission/ to the env	Atmos	sphere	Acidification (SO2 equivalent)	kg	1.37E-01	1.69E-02	1.69E-02	1.12E-01	2.99E-02	3.13E-01

- A. "Production" stage is intended for two sub-stages listed below
- (1) "Raw material" production: consists of mining, transportation and raw material production. (2) "Product" production: consists of the parts processing, assembly and installation.
- B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal

#### II. Inventory analyses

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.

  B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.
- C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

- Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CQ in case of "Global Warming").
- A. Impact "by resource consumption" represents magnitude of impacts to resource depletion.
- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system

#### IV. Data entry format

- A. Exponential notation, after the decimal point to two, should be used.

  B. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

  C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".
- D. Row total of the data is automatically calculated, excluding a row includes "-" item. Row total of such is presented as a blank (no data). (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.

#### [Notes for readers: Target product specific]

- 1. Product weight includes a ink cartridge, and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

  2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly.
- In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery.

  3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.
- The transportation distance in Japan uses 100 km as average distance.

  4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48000 sheets and printing 48000 sheets by receiving.
- This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month. It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days,
- not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.
- The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included The distribution impact of consumables is calculated under the same condition of products:
- The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance.
- Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.
- 5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

# Product data sheet

(Input data and parameters for LCA)

	(input data and parameters for 2011)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-11-114



PSC name	Facsimile(PCR ID:AH-03)	Product type	MFC-J6710CDW					
LCA/LCIA in units of:	1	Product weight (kg)	17.6	Package (kg)	5.43	weight total (kg)	23.0	

1. Product information (per unit): parts etc. by material and by process/assembly method

		Breakdown of p	rimary materials		Math breakdown of parts, which need to apply Processing / Assembly base Units (Parts B,C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
	Steel	3.24E+00	Paper	5.27E+00	Press molding: Iron (kg)	3.34E+00	Parts assembly (kg)	5.14E+00	
#	Stainless steel	5.53E-02	Semiconductor substrate	8.24E-01	Press molding: Nonferrous metal (kg)	5.28E-03			
duct	Aluminum	3.42E-03	Wood	0	Injection molding (kg)	1.18E+01			
l 2	Other metal	5.23E-02	Medium-sized motor	3.60E-01	Glass molding (kg)	1.32E+00			
•	Thermoplastic resin	1.14E+01	Alkali-manganese dry battery	3.40E-02					
	Thermosetting resin	6.38E-03	Lubricants	1.71E-03					
	Rubber	4.10E-01	Water	4.06E-02					
	Glass	1.32E+00							
	Subtotal	1.65E+01	Subtotal	6.53E+00					
		Total		2.30E+01	Subtotal	1.65E+01	Subtotal	5.14E+00	
Note	Nickel hydride bettery bee been cale	ulated using the	basis unit of Alkali manageness druk	ottoni					

Note Nickel hydride battery has been calculated using the basic unit of Alkali-manganese dry battery.

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

SOx and NOx should be indicated in  $SO_2$ ,  $NO_2$  equivalent.

	Classification	Material	Material	Energy	Energy	Energy	Energy	Material	Energy
ū	Distribution	Corrugated cardboard (kg)	PP (kg)	Clean water (kg)	Furnace urban gas (13A) (m3)	Electricity (kwh)	Diesel truck: 4 ton (kg.km)	Clean water (kg)	Incineration: Industrial waste (kg)
ફ	Quantity	1.52E-02	2.13E-03	1.73E-01	2.99E-04	8.39E+00	1.85E+00	1.28E+00	1.46E-01
umption	Note								
ns	Classification	Energy	Energy	Material	Energy	Energy			
Con	Distribution	Gasoline as fuel (kg)	Freight by air (kg.km)	Incineration: Industrial waste (kg)	Diesel truck: 10 ton (kg.km)	Freight by ship (kg.km)			
	Quantity	4.14E-02	1.32E+02	1.30E+00	1.24E+01	9.17E+01			
	Note								
) /  -	Classification								
Emission / Discharge	Distribution								
m isc	Quantity								
	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:	Freight by	Freight by	Freight by	Freight by
transportation	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)
Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)
Quantity	2.31E+01	8.50E+01	3.42E+01	5.72E+03	2.31E+01	2.63E+03	1.00E+02	6.06E+04
Note								
Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:				
transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)				
Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
Quantity	2.31E+01	1.00E+02	3.41E+01	6.76E+03				
Note								
	transportation  Conditions  Quantity  Note  Means of transportation  Conditions  Quantity	transportation 20 ton (kg.km) Conditions Mass (kg) Quantity 2.31E+01 Note Means of Diesel truck: 10 ton (kg.km) Conditions Mass (kg) Quantity 2.31E+01	transportation         20 ton (kg.km)         20 ton (kg.km)           Conditions         Mass (kg)         Distance (km)           Quantity         2.31E+01         8.50E+01           Note         Means of transportation         Diesel truck: 10 ton (kg.km)           Conditions         Mass (kg)         Distance (km)           Quantity         2.31E+01         1.00E+02	transportation         20 ton (kg,km)         20 ton (kg,km)         20 ton (kg,km)           Conditions         Mass (kg)         Distance (km)         Loading Ratio (%w)           Quantity         2.31E+01         8.50E+01         3.42E+01           Note         Means of transportation         Diesel truck: 10 ton (kg,km)         10 ton (kg,km)         10 ton (kg,km)           Conditions         Mass (kg)         Distance (km)         Loading Ratio (%w)           Quantity         2.31E+01         1.00E+02         3.41E+01	transportation         20 ton (kg.km)         3.42E+01         5.72E+03           Means of transportation         Diesel truck: 10 ton (kg.km)         20 ton (kg.km)         10 ton (k	transportation         20 ton (kg.km)         20 ton (kg.km)         20 ton (kg.km)         ship (kg.km)           Conditions         Mass (kg)         Distance (km)         Loading Ratio (%w)         Load (kg·km)         Mass (kg)           Quantity         2.31E+01         8.50E+01         3.42E+01         5.72E+03         2.31E+01           Note                 Means of transportation         10 ton (kg.km)         10 ton (kg.km)   <	transportation         20 ton (kg.km)         20 ton (kg.km)         20 ton (kg.km)         ship (kg.km)         ship (kg.km)           Conditions         Mass (kg)         Distance (km)         Loading Ratio (%w)         Load (kg·km)         Mass (kg)         Distance (km)           Quantity         2.31E+01         8.50E+01         3.42E+01         5.72E+03         2.31E+01         2.63E+03           Means of transportation         Diesel truck: 10 ton (kg.km)         Diesel truck: 10 ton (kg.km)         Diesel truck: 10 ton (kg.km)         Diesel truck: 10 ton (kg.km)         Use (kg.km)         U	transportation         20 ton (kg.km)         20 ton (kg.km)         20 ton (kg.km)         ship

Note

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

		sasones subject to							
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Stainless steel plate (kg)	Low density polyethylene (kg)	PP (kg)	POM(polyacetal) (kg)
	Quantity	1.70E+02	4.13E+02	1.23E+04	7.43E+02	1.54E-02	1.10E-01	1.39E+00	3.53E-01
		Electricity	Distribution of	Distribution of	Distribution of				
	Note	consumption for	consumables used in	consumables used in	consumables used in				
		5 years	5 years	5 years	5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
duct	Distribution	ABS (kg)	PET (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	Clean water (kg)	Injection molding (kg)
2	Quantity	3.19E-01	2.04E-01	1.30E-02	1.59E-01	7.31E-01	1.61E-02	6.74E+00	2.39E+00
•	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Process			
	Distribution	Press molding: Iron (kg)	Electricity (kwh)	Urban gas (m3)	Gasoline as fuel (kg)	Incineration: Industrial waste (kg)			
	Quantity	1.54E-02	1.34E+00	9.45E-03	3.83E-03	4.61E+00			
			Production of	Production of	Production of	Production of			
	Note		consumables used in	consumables used in	consumables used in	consumables used in			
			5 years	5 years	5 years	5 years			

Note Electric power consumption in 5 years of "Use stage" is 170kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

4.2	2 Disposition/Recycle information on consumables and replacement parts													
	3S	Classification	Consumption	Process	Process	Process								
	ğ	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:								
	ma		4 ton (kg.km)	Siliedding (kg)	landfill	General waste (kg)								
	su	Quantity	2.22E+02	6.14E-01	2.28E+00	1.79E-02								
	Cons	Note	Consumables not	Consumables not	Consumables not	Consumables not								
		Note	collected	collected	collected	collected								

5. Disposition/Recycle stage information (per product): process method and scenarios

o. Disp	Disposition/Necycle stage information (per product). process method and scenarios												
	Classification	Consumption	Process	Process	Process								
.9	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:								
٦		4 ton (kg.km)		landfill (as ash) (kg)	General waste (kg)								
9	Quantity	2.20E+03	1.73E+01	1.68E+01	5.89E+00								
ű	Note	Machines not	Machines not	Machines not	Machines not								
	NOTE	collected	collected	collected	collected								