## Product Environmental Aspects Declaration

Facsimile (PCR number: AH-03)



No. AH-11-115
Date of publication
May/17/2011

# brother at your side

### http://www.brother.co.jp/

For inquiry:

Product Environmental Group Environmental Management Dept. Brother Industries, Ltd.

Tel: +81-52-824-2735 FAX: +81-52-824-5667




## A3 Color Multi-Function Center **MFC-J6910CDW** Specifications:

- · Color Inkjet Printing
- Business Use
- Recording Paper Size: A3 (Max. 297 x 420mm)
- Original Sheet Size: Max-width 297mm
- Modem Speed: 33,600 bps (Automatic switchover)
- Duplex Printing

The following data is calculated by assuming the product sends and receives both 48,000 sheets in 5-year usage period.

- < Main environmental impact in the product lifecycle >
- Energy consumption 4,320MJ
- Global warming impact (CO<sub>2</sub> equivalent)
- 238kg
- Acidification impact (SO<sub>2</sub> equivalent)
   0.335kg



- Electric power consumption in 5 years of "Use stage" is 186kWh.
- The above data does not include the environmental impact of the paper that is used for printing.

#### Notes:

- 1. Original LCA data is available on PEIDS: Product Environmental Information Declaration Sheet, and Product Data Sheet.
- 2. Unified rules and requirements for EcoLeaf LCA, for intended product category, are available as a PCR: Product Category Rule. Visit EcoLeaf website under JEMAI homepage at http://www.jemai.or.jp/ecoleaf\_e/ for details.
- 3. The units used for EcoLeaf calculations are based on Japanese domestic data. Overseas data has not been applied.

## [Supplemental environmental information]

The product assembly and main parts of ink and inkjet head are produced at plants certified with ISO 14001.

The product conforms to the International Energy Star Program.

The product has obtained the ECO Mark certification (3R & Energy-Saving Design).

PCR review was conducted by: PCR Deliberation Committee, February 01, 2011, Name of representative : Yohji Uchiyama, University of Tsukuba, Graduate School

Independent verification of the label and data, according to ISO 14025:2006 ☐ internal ■ external Third party verifier \*: Shozo Nakamuta

Program operator: Japan Environmental Management Association for Industry Email: ecoleaf@jemai.or.jp

<sup>\*</sup> In the case of a business entity certified as an Ecoleaf-data-collection system, the names of certification auditors are written.

#### Product Environmental Information Data Sheet (PEIDS)



Document control no.	F-02As-02
Product vendor	Brother Industries,LTD.
EcoLeaf registration no.	AH-11-115

Unit Function DB versio Characterization Factor DB versio

n	v2.1
n	v2.1

PCR name	Facsimile		Product type	MFC-J6910CDW				
PCR code	AH-03	Product weight (kg)	17.9	Package (kg)	5.44	Weight total (kg)	23.4	

	Life Cycle Stag					Produ	ıction				
In/Out	items				Unit	Raw material	Product	Distribution	Use	Disposal	Total
		F	0	umption	MJ	2.01E+03	2.21E+02	5.75E+01	2.01E+03	2.50E+01	4.32E+03
		Energ	y Cons	umption	Mcal	4.80E+02	5.29E+01	1.37E+01	4.80E+02	5.97E+00	1.03E+03
			es <	Coal	kg	8.48E+00	1.45E+00	1.34E-04	1.05E+01	1.52E-01	2.06E+01
			Energy resources	Crude oil (for fuel)	kg	1.98E+01	1.77E+00	1.26E+00	1.34E+01	2.64E-01	3.64E+01
			Sou	LNG	kg	3.88E+00	7.27E-01	1.94E-02	5.62E+00	7.79E-02	1.03E+01
			Fre	Uranium content of an ore	kg	3.50E-04	9.80E-05	9.10E-09	7.08E-04	1.02E-05	1.17E-03
				Crude oil (for material)	kg	1.13E+01	2.12E-03	0	2.14E+00	0	1.35E+01
				Iron content of an ore	kg	3.92E+00	0	0	5.01E-03	0	3.93E+00
		Exhaustible resources		Cu content of an ore	kg	2.10E-01	0	0	0	0	2.10E-01
	9	n n		Al content of an ore	kg	3.53E-02	0	0	0	0	3.53E-02
	Impact by Resource Consumption	Sec	v	Ni content of an ore	kg	9.07E-03	0	0	2.43E-03	0	1.15E-02
	eact by Resou Consumption	9 16	Ce	Cr content of an ore	kg	1.35E-02	0	0	3.29E-03	0	1.68E-02
	8 E	ible	ınc	Mn content of an ore	kg	3.75E-02	0	0	4.18E-04	0	3.79E-02
	by Isu	ust	esi	Pb content of an ore	kg	1.26E-02	0	0	0	0	1.26E-02
	o act	ha	<u>=</u>	Sn content of an ore	kg	-	-	-	-	-	
	gu O	Ĕ		Zn content of an ore	kg	1.24E-01	0	0	0	0	1.24E-01
	=			Au content of an ore	kg	-	-	-	-	-	
				Ag content of an ore	kg	-	-	-	-	-	
				Silica Sand	kg	1.33E+00	0	0	3.23E-05	0	1.33E+00
es				Halite	kg	8.40E-01	1.45E-03	0	4.91E-03	7.07E-03	8.54E-01
nventory anaiyses				Limestone	kg	1.37E+00	9.37E-02	0	3.29E-01	2.14E-01	2.00E+00
Jai			aahla	Natural soda ash	kg	1.43E-01	0	0	0	0	1.43E-01
ਲ		Rene	wable	Wood	kg	1.16E+01	3.24E-02	0	2.05E+00	0	1.36E+01
<u></u>		resou	urces	Water	kg	8.94E+03	1.10E+03	1.01E-01	8.25E+03	1.29E+02	1.84E+04
į				CO2	kg	9.77E+01	1.38E+01	4.08E+00	9.61E+01	2.30E+01	2.35E+02
Se Se				SOx	kg	5.51E-02	9.77E-03	2.55E-03	6.89E-02	1.20E-02	1.48E-01
=				NOx	kg	1.36E-01	1.02E-02	2.06E-02	7.33E-02	2.56E-02	2.66E-01
		+	^	N2O	kg	9.68E-03	1.79E-04	6.68E-04	1.69E-03	3.24E-05	1.22E-02
	e g	to Atmosphere		CH4	kg	9.35E-04	2.62E-04	2.43E-08	1.89E-03	2.74E-05	3.12E-03
	Emission/Discharge e environment			CO	kg	1.08E-02	1.99E-03	5.61E-03	1.43E-02	4.63E-03	3.73E-02
	당			NMVOC	kg	1.83E-03	5.13E-04	4.76E-08	3.71E-03	5.37E-05	6.10E-03
	e Dis			СхНу	kg	4.52E-03	5.99E-05	6.02E-04	6.15E-04	8.43E-05	5.89E-03
	/uc			Dust	kg	1.36E-02	3.74E-04	1.94E-03	3.88E-03	1.45E-03	2.12E-02
	SSic			BOD	kg	-	1	-	1	-	
	mis en	to	^	COD	kg	-	-	-	-	-	
	y Emission/Discl the environment	Water		N total	kg	-	-	-	-	-	
	t by	water	JUITIAIIT	P total	kg	-	-	-	-	-	
	act			SS	kg	-	-	-	-	-	
	Impact by to th			Unspecified Solid Waste	kg	1.03E+00	5.44E-04	0	6.56E-01	8.85E+00	1.05E+01
	=			Slag	kg	1.48E+00	0	0	3.14E-03	0	1.48E+00
			0	Sludge	kg	7.76E-03	0	0	0	0	7.76E-03
		Soil s	ystem	Low level							
				radio-active waste	kg	2.45E-04	6.84E-05	6.36E-09	4.94E-04	7.16E-06	8.14E-04
				radio-active waste							
	e =			Energy resources							
	otic			(crude oil equivalent)	kg	3.27E+01	4.37E+00	1.28E+00	3.27E+01	5.39E-01	7.16E+01
	by Resource Consumption		ustible	(1.113 on oquiralont)							
+	' Re	resou	ırces	Mineral resources	le=	7.005.04	1 175 00	0	3 105 : 00	0	7.205.04
e x	රි රි			(Iron ore equivalent)	kg	7.08E+01	1.17E-03	0	3.10E+00	0	7.39E+01
Impact assessment				,							
mg	arg			Global Warming	k-	1.00E+02	1 205 : 01	4.265.00	0.665+01	2.20E+04	2.39E+02
-	by Sch			(CO2 equivalent)	kg	1.00E+02	1.38E+01	4.26E+00	9.66E+01	2.30E+01	2.38E+02
(0	Impact by sion/Disch e environ	t o									
	Impact by Emission/Discharge to the environment	Atmos	spnere	Acidification							
	mis:			(SO2 equivalent)	kg	1.51E-01	1.69E-02	1.70E-02	1.20E-01	2.99E-02	3.35E-01
	回口	tot									

[Notes for readers: EcoLeaf common rules]

- "Production" stage is intended for two sub-stages listed below.

- (1) "Raw material" production: consists of mining, transportation and raw material production.
  (2) "Product" production: consists of the parts processing, assembly and installation.

  B. "Distribution" stage is intended for transportation of produced product. Transportation of consumables and maintenance goods (e.g., replacement parts) for use of the product are included into "Use" stage.
- C. "Use" stage in intended for use of the product (active mode, standby mode, etc.) and production, transportation to disposal of consumables/maintenance goods (e.g., replacement parts).
- D. "Disposal" stage in intended for environmental impacts by product disposal.

- A. Data of mineral ore on "Exhaustible resources" are presented in weight of pure ingredients (e.g., iron, aluminum) in the ore.

  B. Data on energy resources are presented based on origin in calorific value. e.g. Data on uranium ore presents weight of uranium concentrate, which is available for use as an atomic fuel.

  C. Data of discharge to water system are in actual figure (not calculated using unit function in inventory analyses).

III. Impact analyses

Result of the "Impact analyses" is found in converting results of inventory analyses into total amount of a reference material (e.g. CQ in case of "Global Warming").

- B. Impact "by emission/discharge to environment" represents magnitude of impacts to Atmosphere, Water and Soil system.

- A. Exponential notation, after the decimal point to two, should be used.
- R. Indicate "0" instead exponential notation, if the result of calculation or estimation is considered as "zero" or negligible in comparison to related results.

  C. Indicate "—" if calculation nor estimation can not be done, in order to differentiate to indicate "zero".

  D. Row total of the data is automatically calculated, excluding a row includes "—" item. Row total of such is presented as a blank (no data).
- (BGD for material production are for production from mineral ore. Those data do not include reclaiming processes like recovery from scrap.

#### [Notes for readers: Target product specific]

- 1. Product weight includes a ink cartridge, and other accessories. Packaging weight includes packaging material and appended goods (e.g., user's manual, other printed matter).

  2. Production stage includes the production/distribution impact of the parts making up a machine and the initial set of a toner cartridge and a photo conductor, as well as the impact of product assembly. In the production impact of raw material, the impact of a Ni-MH battery is calculated using the basic impact rate of an alkaline-manganese battery.

  3. Distribution stage's impact is calculated according to the PCR. The transportation distance of a product from an overseas factory to the port of Japan is based on actual distance.
- The transportation distance in Japan uses 100 km as average distance.
- 4. Use stage's impact is calculated according to the PCR. It includes the impact of fax transmitting 48000 sheets and printing 48000 sheets by receiving.

  This number is calculated by supposing a user use a machine for 5 years, sending 5 sheets an hour, receiving 5 an hour, operating a machine 8 hours a day, 20 days a month.

It also includes the electricity consumption of a machine calculated based on 5-year use, supposing a year consists of 365 days, not taking a leap year into consideration, supposing a machine is on standby all the time when it is not used.

- The production, distribution, and disposal/recycle impact of the consumables used in those 5 years is also included
- The distribution impact of consumables is calculated under the same condition of products:

The transportation distance of consumables from an overseas factory to the port of Japan is based on actual distance. The transportation distance in Japan uses 100 km as average distance. Since we have no past record of consumables collection/recycle in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible mate. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of consumables.

5. Disposal stage: Since we have not collected machines as a producer in Japan, they are assumed to be collected as general waste, crushed and separated as combustible/non-combustible material. This stage includes the incineration impact of combustible materials and the landfill impact of non-combustible materials of machines.

## **Product data sheet**

(Input data and parameters for LCA)

	(input data dila parametere for 2011)
Document control no.	F-03s-02
Product vendor	Brother Industries,LTD.
EcoLEaf registration no.	AH-11-115



PSC name	Facsimile(PCR ID:AH-03)	Product type	MFC-J6910CDW					
LCA/LCIA in units of:	1	Product weight (kg)	17.9	Package (kg)	5.44	weight total (kg)	23.4	

1. Product information (per unit): parts etc. by material and by process/assembly method

		Proakdown of n	rimary materials			Math breakd			
					which need to apply Processing / Assembly base Units (Parts B,C)				
	Material name	Weight (kg)	Material name	Weight (kg)	Process name	Weight (kg)	Process name	Weight (kg)	
	Steel	3.30E+00	Paper	5.30E+00	Press molding: Iron (kg)	3.43E+00	Parts assembly (kg)	5.13E+00	
*	Stainless steel	5.70E-02	Semiconductor substrate	1.00E+00	Press molding: Nonferrous metal (kg)	5.63E-03			
duct	Aluminum	3.42E-03	Wood	0	Injection molding (kg)	1.18E+01			
ĕ	Other metal	7.36E-02	Medium-sized motor	3.60E-01	Glass molding (kg)	1.40E+00			
₫.	Thermoplastic resin	1.14E+01	Alkali-manganese dry battery	3.40E-02					
	Thermosetting resin	6.38E-03	Lubricants	1.71E-03					
	Rubber	4.07E-01	Water	4.06E-02					
	Glass	1.40E+00							
	Subtotal	1.66E+01	Subtotal	6.74E+00					
		Total		2.34E+01	Subtotal	1.66E+01	Subtotal	5.13E+00	

Note Nickel hydride battery has been calculated using the basic unit of Alkali-manganese dry battery.

2. Production site information (per unit): Consumption and discharge/emission for production/processing/assembly within the site.

	Classification	Material	Material	Energy	Energy	Energy	Energy	Material	Energy
Ē	Distribution	Corrugated cardboard (kg)	PP (kg)	Clean water (kg)	Furnace urban gas (13A) (m3)	Electricity (kwh)	Diesel truck: 4 ton (kg.km)	Clean water (kg)	Incineration: Industrial waste (kg)
tion	Quantity	1.52E-02	2.13E-03	1.73E-01	2.99E-04	8.39E+00	1.85E+00	1.28E+00	1.46E-01
ᇤ	Note								
ns	Classification	Energy	Energy	Material	Energy	Energy			
Con	Distribution	Gasoline as fuel (kg)	Freight by air (kg.km)	Incineration: Industrial waste (kg)	Diesel truck: 10 ton (kg.km)	Freight by ship (kg.km)			
	Quantity	4.14E-02	1.32E+02	1.30E+00	1.24E+01	9.17E+01			
	Note								
-/ e	Classification								
ssion	Distribution								
Emis Discl	Quantity								
П	Note								

Note

3. Distribution stage information (per unit): means, distance, loading ratio, consumptions and emissions/discharges.

. Distri	istribution stage information (per unit). Ineans, distance, loading ratio, consumptions and emissions/discharges.												
	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:	Freight by	Freight by	Freight by	Freight by				
	transportation	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	20 ton (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)	ship (kg.km)				
_	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)				
.0	Quantity	2.34E+01	8.50E+01	3.47E+01	5.72E+03	2.34E+01	2.63E+03	1.00E+02	6.15E+04				
Ιğ	Note												
1 Ē	Means of	Diesel truck:	Diesel truck:	Diesel truck:	Diesel truck:								
is	transportation	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)	10 ton (kg.km)								
-	Conditions	Mass (kg)	Distance (km)	Loading Ratio (%w)	Load (kg·km)								
	Quantity	2.34E+01	1.00E+02	3.46E+01	6.76E+03								
	Note						_						

4. Use stage (per unit): use condition (mode, term) including active mode, standby mode and maintenance.

4.1 Product and accessories subject to this analysis

	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
	Distribution	Electricity (kwh)	Diesel truck: 20 ton (kg.km)	Freight by ship (kg.km)	Diesel truck: 10 ton (kg.km)	Stainless steel plate (kg)	Low density polyethylene (kg)	PP (kg)	POM(polyacetal) (kg)
	Quantity	1.86E+02	4.13E+02	1.23E+04	7.43E+02	1.54E-02	1.10E-01	1.39E+00	3.53E-01
		Electricity	Distribution of	Distribution of	Distribution of				
	Note	consumption for	consumables used in	consumables used in	consumables used in				
		5 years	5 years	5 years	5 years				
	Classification	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption	Consumption
uct	Distribution	ABS (kg)	PET (kg)	Nitrile-butadiene rubber (NBR) (kg)	Corrugated cardboard (kg)	Cardboard (kg)	Paper (Western style)	Clean water (kg)	Injection molding (kg)
rodu	Quantity	3.19E-01	2.04E-01	1.30E-02	1.59E-01	7.31E-01	1.61E-02	6.74E+00	2.39E+00
ď	Note								
	Classification	Consumption	Consumption	Consumption	Consumption	Process			
	Distribution	Press molding: Iron (kg)	Electricity (kwh)	Urban gas (m3)	Gasoline as fuel (kg)	Incineration: Industrial waste (kg)			
	Quantity	1.54E-02	1.34E+00	9.45E-03	3.83E-03	4.61E+00			
			Production of	Production of	Production of	Production of			
	Note		consumables used in	consumables used in	consumables used in	consumables used in			
			5 years	5 years	5 years	5 years			

Note Electric power consumption in 5 years of "Use stage" is 186kWh.

4.2 Disposition/Recycle information on consumables and replacement parts

7.2	Disp	osition/itecy	cie illiorillation on	consumables and i	cpiacement parts				
	Se	Classification	Consumption	Process	Process	Process			
:	ğ [	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:			
	E l		4 ton (kg.km)	Silledding (kg)	landfill	General waste (kg)			
	ns	Quantity	2.22E+02	6.14E-01	2.28E+00	1.79E-02			
	Cons	Note	Consumables not	Consumables not	Consumables not	Consumables not			
			collected	collected	collected	collected	1		

. Diop	oonion, recoyo	ic stage information	(per product), pro-	ocoo memoa ana oc	orianio o		
	Classification	Consumption	Process	Process	Process		
.0	Distribution	Diesel truck:	Shredding (kg)	Incineration to	Landfill:		
ā		4 ton (kg.km)	Officading (kg)	landfill (as ash) (kg)	General waste (kg)		
ĕ	Quantity	2.23E+03	1.76E+01	1.68E+01	6.24E+00		
ŭ	Note	Machines not	Machines not	Machines not	Machines not		
		collected	collected	collected	collected		i

Note

Note